



SECTION A-A SCALE 41

01	0	0
02	.100	1
03	.200	5
04	.300	3
05	.400	4
06	.500	5
07	.600	6
80	.700	7
09	.800	8
10	.900	9
11	1.000	10
12	1.100	11
13	1.200	12
14	1.300	13
15	1.400	14
16	1.500	15
17	1.600	16
18	1.700	17
19	1.800	18
20	 1.900	19
21	2.000	20
55	2.100	21
53	2.200	22
24	2.300	53
25	2.400	24
26	2.500	25
27	 2.600	26
28	2.700	27
29	2.800	58
30	2.900	29
31	3.000	30
35	3.100	31

PART NUMBER (SEE TABLES)

cage code

TABLE 1

DIMENSION

"Y" "X"

PART NUMBER

2(XXX) - [<1] X 1-T22

NOTES:

NUMBER OF CONTACTS PER ROW (01 TO 32).

2. INSULATOR MATERIAL:

GLASS REINFORCED POLYPHENYLENE SULFIDE (PPS) RATED UL 94V-0, COLOR BLACK.

- 3. CONTACT MATERIAL:
- DUTER SHELL: BRASS ALLOY 360, 1/2 HARD PER QQ-B-626.
- 4. CONTACT PLATING:

TIN/LEAD PER MIL-P-81728 TYPE 1,

NICKEL PER QQ-N-290.

GOLD PER MIL-G-45204, TYPE 1, GRADE C.

			SST-1 X [[>] - [XXX
mat'l. code	tolerances unless otherwise specified	CUSTOMER	# Electronics

ltr_	ecn no	dr	date	linear			KX 3	<u> </u>		00, 1			FCI			www.fciconnect.com			
Α	V00765	DLW	3/10/00			.XX	(X ±	.005		proje	ection	ŀ	title		-				
				1			(X ±	.002	0			Sit	NGLE	ROW SIF		HEA	NDERS		
	}	7	I	angle	s	0° ±2°			7	ァマ	7	<u>L</u> _							
				dr	D.	WOLF	ORD	3/10	0/00	4 114011		produ	ict family		SIP		code		
Г				engr	A.	VASBIN	IDER	3/10	0/00			-	size	dwg no	_				
				chr	A.	VASBIN	IDER	3/10	0/00	scale	;		۱ ۸	ı	589	\cap		sheet	
	l			appd	A.	VASBIN	IDER	3/10	00\0		2:1		A		202	UJ		1 of	1
she	et rev	ision	Α																
linde	x She	et	11																

PDM: Rev:A

STATUS Released

22526 Printed: Jan 19, 2006

- [XXX]S

В

1 | 2

ACAD