

FEATURES

- Axial Format
- Up to 5.35A IDC
- 4.7 μ H to 10mH
- Low DC Resistance
- Compact Size
- Fully Tinned Leads
- MIL-I-23053/5 Class III Slewing
- Supplied in Packs of 10
- Custom & Radial Parts Available

DESCRIPTION

The 1800 Series of inductors are particularly suited to use with a wide variety of switching regulators. Offering high current handling with a low mounting height, the devices are ideal where space is at a premium.

SELECTION GUIDE						
Order Code	Inductance $\pm 10\%$ (at 1kHz) μ H	DC Resistance m MAX	DC Current Continuous A MAX	Nominal Q at f kHz		Nominal Self Resonant Frequency MHz
				Q	f	
18472	4.7	9	5.35	112	1000	36.4
18682	6.8	12	4.15	78	500	23.6
18103	10	15	3.45	64	500	19.0
18153	15	18	3.00	55	500	15.9
18223	22	25	2.42	59	500	11.8
18333	33	40	2.00	48	500	11.5
18473	47	55	1.65	55	500	8.5
18683	68	70	1.35	31	100	6.6
18104	100	100	1.20	40	100	7.4
18154	150	165	1.10	47	100	4.4
18224	220	230	0.90	46	100	3.5
18254	250	255	0.80	50	100	3.7
18334	330	335	0.73	58	100	3.0
18474	470	465	0.60	56	100	2.2
18684	680	630	0.53	55	100	2.0
18105	1mH	1.0	0.44	94	50	1.6
18155	1.5mH	1.5	0.33	107	50	1.3
18225	2.2mH	2.2	0.30	108	50	1.1
18335	3.3mH	3.5	0.22	143	50	0.8
18475	4.7mH	4.6	0.20	128	40	0.7
18685	6.8mH	7.0	0.15	144	40	0.6
18106	10mH	12	0.13	143	40	0.5


TYPICAL CORE CHARACTERISTICS			
Inductance Temperature Coefficient	Resistance Temperature Coefficient	Curie Temperature T_C	Saturation Flux B_{SAT}
450ppm	4000ppm	190°C	325mT

ABSOLUTE MAXIMUM RATINGS	
Operating free air temperature range	0°C to 70°C
Storage temperature range	-55°C to 125°C

1800 SERIES

Axial Lead Inductors

MECHANICAL DIMENSIONS



All dimensions in mm $XX.XX \pm 0.25$

C&D Technologies (NCL) Limited reserve the right to alter or improve the specification, internal design or manufacturing process at any time, without notice. Please check with your supplier or visit our web site to ensure that you have the current and complete specification for your product before use.

© C&D Technologies (NCL) Limited 2000

NMP 1800.2

No part of this publication may be copied, transmitted or stored in a retrieval system or reproduced in any way including, but not limited to, photography, photocopy, magnetic or other recording means, without prior written permission from C&D Technologies (NCL) Limited.

Instructions for use are available from www.dc-dc.com

C&D Technologies (NCL) Ltd
Tanners Drive, Blakelands North
Milton Keynes MK14 5BU, England
Tel: +44 (0)1908 615232
Fax: +44 (0)1908 617545
email: info@cdtechno-ncl.com

www: <http://www.dc-dc.com>

C&D Technologies (NCL), Inc.
8917 Glenwood Avenue, Raleigh
NC 27612, USA
Tel: +1 (919) 571-9405
Fax: +1 (919) 571-9262
email: info@us.cdtechno-ncl.com

C&D TECHNOLOGIES
Power Solutions