

<h3>0385</h3> <p><b>0385-0-15-XX-43-XX-10-0</b> Press-fit in 1,17 mounting hole</p>	<h3>4001</h3> <p><b>4001-0-15-XX-43-XX-04-0</b> Press-fit in 1,45 mounting hole</p>	<h3>1782</h3> <p><b>1782-0-15-XX-43-XX-04-0</b> Press-fit in 1,14 mounting hole</p>	<h3>5960</h3> <p><b>5960-0-15-XX-43-XX-04-0</b> Hex press-fit in 1,45 plated thru hole</p>
---	---	---	--

<h3>1401/3185</h3> <p><b>XXXX-0-15-XX-30-XX-10-0</b> Solder mount in 1,4 min. mounting hole Also available on 16mm wide carrier tape: 1,700 parts per 330mm reel. Order as: XXXX-0-57-XX-30-XX-10-0</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Depth N</th> <th>Length L</th> </tr> </thead> <tbody> <tr> <td>1401-0</td> <td>3,68</td> <td>4,19</td> </tr> <tr> <td>3185-0</td> <td>2,77</td> <td>3,30</td> </tr> </tbody> </table>	Basic Part Number	Depth N	Length L	1401-0	3,68	4,19	3185-0	2,77	3,30	<h3>4310</h3> <p><b>4310-0-31-XX-43-XX-04-0</b> Compliant press-fit in 1,02±0,08 plated hole. For 2,29→3,30 thick board.</p>	<h3>1385</h3> <p><b>1385-0-15-XX-43-XX-10-0</b> Surface mount</p>
Basic Part Number	Depth N	Length L										
1401-0	3,68	4,19										
3185-0	2,77	3,30										

<h3>3018</h3> <p><b>3018-0-15-XX-30-XX-04-0</b> Press-fit in 1,45 mounting hole</p>	<h3>8852</h3> <p><b>8852-0-15-XX-30-XX-04-0</b> Press-fit in 1,42 mounting hole</p>	<h3>3907</h3> <p><b>3907-0-18-XX-30-XX-10-0</b> Surface mount Also available on 12mm wide carrier tape: 4,000 parts per 330mm reel. Order as: 3907-0-58-XX-30-XX-10-0</p>	<p><b>P.C.B. Layout</b></p>
---	---	---	-----------------------------

<h3>SPECIFICATIONS</h3> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES TOLERANCES ON:</b> LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - XX - XX - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <ul style="list-style-type: none"> <li>01 5,08µm TIN/LEAD OVER NICKEL</li> <li>◇ 80 5,08µmTIN OVER NICKEL (RoHS)</li> <li>◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SPECIFY CONTACT FINISH:</b></p> <ul style="list-style-type: none"> <li>02 2,54µm TIN/LEAD OVER NICKEL</li> <li>◇ 84 2,54µm TIN OVER NICKEL (RoHS)</li> <li>◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SELECT CONTACT</b> #30, #35 or #43 CONTACT (DATA ON PAGES 219 &amp; 220)</p>
--	---