


Surface Mount

Monolithic Amplifiers

NEW!

Gali-19 • Gali-29 • Gali-39
Gali-49 • Gali-59

50Ω, Broadband, DC to 7 GHz



CASE STYLE : DF782

Features

- miniature SOT-89 package
- frequency range, DC to 7 GHz
- up to 17.6 dBm typ. output power
- excellent package for heat dissipation, exposed metal bottom

Applications

- cellular
- PCS
- communication receivers & transmitters

Electrical Specifications @ 25°C

MODEL NO.	FREQ.▲ (GHz)	GAIN, dB Typical									MAXIMUM POWER, dBm at 7 GHz*			DYNAMIC RANGE at 2 GHz*		VSWR (:1) Typ.				MAXIMUM CURRENT RATING**	DC OPERATING POWER @ Pin 3***				THERMAL RESISTANCE θjc, typ. °C/W	PRICE \$ Qty. (25)	
		over frequency, GHz								Min. @ 2 GHz	Output (1 dB Comp.) Typ. Min.	Input (no dmg.)	NF Typ. dB	IP3 Typ. dBm	In DC-3 GHz	3-f _U GHz	Out DC-3 GHz	3-f _U GHz	I mA		Current (mA)	Device Volt	Typ	Min			Max
LOW POWER	Gali-19	DC-7	12.1	11.7	11.6	10.7	10.8	10.1	11.0	14.5	9.6	10.6	9.0	15	6.5	23.7	1.6	1.7	1.5	2.3	55	40	3.6	3.2	4.0	311	1.19
	Gali-29	DC-7	15.4	15.1	14.7	13.7	13.6	12.9	14.2	12.5	11.2	10.0	15	6.0	24.7	1.5	1.6	1.5	2.3	55	40	3.6	3.2	4.0	340	1.19	
	Gali-39	DC-7	20.8	21.1	19.7	17.7	17.0	16.1	17.6	9.8	17.7	10.5	9.0	13	4.9	22.9	1.6	1.8	1.5	2.3	55	35	3.5	3.1	3.9	350	1.19
MEDIUM POWER	Gali-49	DC-5	14.0	13.7	13.6	13.7	13.3	13.1	10.7	—	11.5	16.4	15.0	20	5.5	33.3	1.7	1.2	1.5	1.4	85	65	5.0	4.5	5.4	171	1.79
	Gali-59	DC-5	20.6	19.7	18.3	16.7	15.4	14.0	10.2	—	16.3	17.6	16.5	13.0	4.3	33.3	1.6	1.5	1.5	1.7	85	65	4.8	4.3	5.2	209	1.79

▲ Low frequency cutoff determined by external coupling capacitors.
* For Pout @ 1dB compression, Gali-49,-59 at 2 GHz.
For IP3, Gali-49,-59 at 1 GHz.
** Permanent damage may occur if any of these limits are exceeded.
These ratings are not intended for continuous normal operation.
***Reliability predictions and normal operating conditions are applicable at current specified.

f_U is the upper frequency limit for each model as shown in the table.

Maximum Ratings

Operating Temperature -45°C to 85°C
Storage Temperature -65°C to 150°C


Pin Configuration

RF IN	1
RF OUT	3
DC	3
GND EXT.	2

Model Identification

Model	Marking†
Gali-19	19
Gali-29	29
Gali-39	39
Gali-49	49
Gali-59	59

† Prefix letter (optional) designates assembly location. Suffix letters (optional) are for wafer identification.



INTERNET <http://www.minicircuits.com>


P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010


ISO 9001 CERTIFIED

REV. B
M89969
D60-1117/DOC
Gali-19 Q0201030
Gali-29 Q0201031
Gali-39 Q0201032
Gali-49 EC-9381/10
Gali-59 EC-9381/11
RS/TD/CP
031202

Suggested Layout for PCB Pattern




Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
.102	.090	.181	.173	.063	.167	.155	.059
2.59	2.29	4.60	4.39	1.60	4.24	3.94	1.50
J	K	L	M	N	P	wt. grams	
.118	.015	.041	.016	.019	.065	.2	
3.00	0.38	1.04	0.41	0.48	1.65		

Typical Biasing Configuration



Test Board includes case, connectors, and components (in bold) soldered to PCB

R BIAS

"1%" Resistor Values (ohms) for Optimum Biasing of Gali Models

Vcc	Gali-19	Gali-29	Gali-39	Gali-49	Gali-59
7	88.7	88.7	107	34.0	36.5
8	113	113	133	48.7	51.1
9	137	137	162	64.9	64.9
10	162	162	191	80.6	80.6
11	187	187	221	95.3	97.6
12	215	215	249	110	113
13	237	237	280	127	127
14	261	261	309	143	143
15	287	287	340	158	158
16	309	316	365	174	174
17	332	340	392	187	191
18	357	365	422	205	205
19	383	392	453	221	221
20	412	412	475	237	237