

RF CERAMIC CHIP INDUCTORS



High frequency multi-layer chip inductors feature a monolithic body made of low loss ceramic and high conductivity metal electrodes to achieve optimal high frequency performance.

These RF chip inductors are compact in size and feature lead-free tin plated nickel barrier terminations and tape and reel packaging which makes them ideal for small size/high volume wireless applications.

APPLICATIONS & FEATURES


- CELL/PCS Modules
- Broadband Components
- RF Tranceivers
- RoHS Compliant (Standard, "V" Code)
- Sn/Pb Terminations Optional ("T" Code)
- Wireless LAN
- RFID
- 0201 Mini. Size Available

PRODUCT RANGE SUMMARY

EIA SIZE (mm)	SIZE CODE	L RANGE	Q FACTOR (Min.)	SRF (Typ.)	TEMPERATURE
01005 (0402)	L-03	1.0 - 3.9 nH	TBD	>21 GHz (1.0 nH)	-40°C to + 100°C
0201 (0603)	L-05	0.8 - 39 nH	4 (100 MHz)	>21 GHz (1.0 nH)	-40°C to + 100°C
0402 (1005)	L-07	1.0 - 120 nH	8 (100 MHz)	>21 GHz (1.0 nH)	-40°C to + 100°C
0603 (1608)	L-14	1.0 - 220 nH	12 (100 MHz)	>23 GHz (1.0 nH)	-40°C to + 100°C
0805 (2012)	L-15	1.5 - 680 nH	8 (100 MHz)	>21 GHz (1.5 nH)	-40°C to + 100°C

MECHANICAL CHARACTERISTICS

	01005 (0402)		0201 (0603)		0402 (1005)		0603 (1608)		0805 (2012)	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
Length	.016 ± TBD	(0.4 ± TBD)	.024 ± .001"	(0.6 ± 0.03)	.039 ± .004"	(1.00 ± .10)	.063 ± .006"	(1.60 ± .15)	.079 ± .008"	(2.00 ± .20)
Width	.008 ± TBD	(0.2 ± TBD)	.012 ± .001"	(0.3 ± 0.03)	.020 ± .004"	(0.50 ± .10)	.031 ± .006"	(0.80 ± .15)	.047 ± .008"	(1.20 ± .20)
Thickness	.008 ± TBD	(0.2 ± TBD)	.012 ± .001"	(0.3 ± 0.03)	.020 ± .004"	(0.50 ± .10)	.031 ± .006"	(0.80 ± .15)	.033 ± .008"	(0.85 ± .20)
End Band	TBD		.006 ± .002"	(0.15 ± 0.05)	.009 ± .004"	(0.23 ± .10)	.012 ± .008"	(0.30 ± .20)	.020 ± .012"	(0.50 ± .30)



HOW TO ORDER

L-	07	C	10N	J	V	6	T																									
DEVICE	SIZE	TYPE	VALUE	TOLERANCE	TERMINATION	MARKING	TAPE & REEL																									
Inductor	05 = 0201 07 = 0402 14 = 0603 15 = 0805	Ceramic	See Table	C = ± 0.2 nH ≤ 1.0 nH S = ± 0.3 nH 1.0 to 5.6 nH J = ± 5% 6.8 nH and above K = ± 10% 3.3 nH and above	V = Ni/Sn T = Ni / SnPb	4 = No Marking 6 = Orientation Mark (0402 Only)	<table border="1"> <thead> <tr> <th>Size</th> <th>Code</th> <th>Tape</th> <th>Reel</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>0201</td> <td>T</td> <td>Paper</td> <td>7"</td> <td>15,000</td> </tr> <tr> <td>0402</td> <td>T</td> <td>Paper</td> <td>7"</td> <td>10,000</td> </tr> <tr> <td>0603</td> <td>E</td> <td>Embossed</td> <td>7"</td> <td>4,000</td> </tr> <tr> <td>0805</td> <td>E</td> <td>Embossed</td> <td>7"</td> <td>4,000</td> </tr> </tbody> </table>	Size	Code	Tape	Reel	Qty	0201	T	Paper	7"	15,000	0402	T	Paper	7"	10,000	0603	E	Embossed	7"	4,000	0805	E	Embossed	7"	4,000
Size	Code	Tape	Reel	Qty																												
0201	T	Paper	7"	15,000																												
0402	T	Paper	7"	10,000																												
0603	E	Embossed	7"	4,000																												
0805	E	Embossed	7"	4,000																												

Part number written: L-07C10NJV6T

01005 INDUCTANCE RANGE / ELECTRICAL CHARACTERISTICS

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-03C1N0SV4T	1.0 nH	+/- 0.3 nH	TBD	100 MHz	> 13000 MHz	TBD	200 mA
L-03C1N2SV4T	1.2 nH	+/- 0.3 nH	TBD	100 MHz	> 13000 MHz	TBD	200 mA
L-03C1N8SV4T	1.8 nH	+/- 0.3 nH	TBD	100 MHz	> 13000 MHz	TBD	200 mA
L-03C2N2SV4T	2.2 nH	+/- 0.3 nH	TBD	100 MHz	TBD	TBD	200 mA
L-03C2N7SV4T	2.7 nH	+/- 0.3 nH	TBD	100 MHz	TBD	TBD	200 mA
L-03C3N3SV4T	3.3 nH	+/- 0.3 nH	TBD	100 MHz	TBD	TBD	200 mA
L-03C3N9SV4T	3.9 nH	+/- 0.3 nH	TBD	100 MHz	TBD	TBD	200 mA

0201 INDUCTANCE RANGE / ELECTRICAL CHARACTERISTICS

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-05C0N8CV4T	0.8 nH	± 0.2 nH	4	100 MHz	>13000 MHz	0.12 Ω	300 mA
L-05C0N9CV4T	0.9 nH	± 0.2 nH	4	100 MHz	>13000 MHz	0.12 Ω	300 mA
L-05C1N0*V4T	1.0 nH	± 0.2 or ± 0.3 nH	4	100 MHz	>13000 MHz	0.12 Ω	300 mA
L-05C1N2*V4T	1.2 nH	± 0.2 or ± 0.3 nH	4	100 MHz	>13000 MHz	0.15 Ω	300 mA
L-05C1N3*V4T	1.3 nH	± 0.2 or ± 0.3 nH	4	100 MHz	>13000 MHz	0.15 Ω	300 mA
L-05C1N5*V4T	1.5 nH	± 0.2 or ± 0.3 nH	4	100 MHz	>13000 MHz	0.18 Ω	300 mA
L-05C1N8SV4T	1.8 nH	± 0.3 nH	4	100 MHz	10500 MHz	0.22 Ω	300 mA
L-05C2N2SV4T	2.2 nH	± 0.3 nH	4	100 MHz	9500 MHz	0.26 Ω	300 mA
L-05C2N3SV4T	2.3 nH	± 0.3 nH	4	100 MHz	9200 MHz	0.28 Ω	300 mA
L-05C2N5SV4T	2.5 nH	± 0.3 nH	4	100 MHz	9000 MHz	0.30 Ω	300 mA
L-05C2N7SV4T	2.7 nH	± 0.3 nH	4	100 MHz	8500 MHz	0.32 Ω	300 mA
L-05C3N3@V4T	3.3 nH	± 0.3 nH ±10%	4	100 MHz	7500 MHz	0.38 Ω	300 mA
L-05C3N6@V4T	3.6 nH	± 0.3 nH ±10%	4	100 MHz	7000 MHz	0.43 Ω	300 mA
L-05C3N7@V4T	3.7 nH	± 0.3 nH ±10%	4	100 MHz	6900 MHz	0.44 Ω	300 mA
L-05C3N9@V4T	3.9 nH	± 0.3 nH ±10%	4	100 MHz	6800 MHz	0.45 Ω	300 mA
L-05C4N7@V4T	4.7 nH	± 0.3 nH ±10%	4	100 MHz	6000 MHz	0.50 Ω	300 mA
L-05C5N6@V4T	5.6 nH	± 0.3 nH ±10%	5	100 MHz	5500 MHz	0.60 Ω	300 mA
L-05C6N8#V4T	6.8 nH	±5% ±10%	5	100 MHz	4800 MHz	0.70 Ω	250 mA
L-05C8N2#V4T	8.2 nH	±5% ±10%	5	100 MHz	4600 MHz	0.90 Ω	250 mA
L-05C10N#V4T	10.0 nH	±5% ±10%	5	100 MHz	4000 MHz	1.20 Ω	250 mA
L-05C12N#V4T	12.0 nH	±5% ±10%	5	100 MHz	3500 MHz	1.30 Ω	250 mA
L-05C13N#V4T	13.0 nH	±5% ±10%	5	100 MHz	3500 MHz	1.35 Ω	250 mA
L-05C15N#V4T	15.0 nH	±5% ±10%	5	100 MHz	3000 MHz	1.40 Ω	250 mA
L-05C18N#V4T	18.0 nH	±5% ±10%	5	100 MHz	2500 MHz	1.50 Ω	200 mA
L-05C22N#V4T	22.0 nH	±5% ±10%	5	100 MHz	2200 MHz	1.80 Ω	200 mA
L-05C27N#V4T	27.0 nH	±5% ±10%	5	100 MHz	1800 MHz	2.00 Ω	200 mA
L-05C33N#V4T	33.0 nH	±5% ±10%	5	100 MHz	1500 MHz	2.30 Ω	200 mA
L-05C39N#V4T	39.0 nH	±5% ±10%	5	100 MHz	1400 MHz	2.50 Ω	200 mA

0402 INDUCTANCE RANGE / ELECTRICAL CHARACTERISTICS

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-07C1N0*V6T	1.0 nH	± 0.2 or 0.3 nH	8	100 MHz	>15000 MHz	0.12 Ω	300 mA
L-07C1N2SV6T	1.2 nH	± 0.3 nH	8	100 MHz	>15000 MHz	0.12 Ω	300 mA
L-07C1N5SV6T	1.5 nH	± 0.3 nH	8	100 MHz	>15000 MHz	0.13 Ω	300 mA
L-07C1N6SV6T	1.6 nH	± 0.3 nH	8	100 MHz	14000 MHz	0.14 Ω	300 mA
L-07C1N8SV6T	1.8 nH	± 0.3 nH	8	100 MHz	14000 MHz	0.14 Ω	300 mA
L-07C1N9SV6T	1.9 nH	± 0.3 nH	8	100 MHz	13000 MHz	0.15 Ω	300 mA
L-07C2N0SV6T	2.0 nH	± 0.3 nH	8	100 MHz	12000 MHz	0.16 Ω	300 mA
L-07C2N2SV6T	2.2 nH	± 0.3 nH	8	100 MHz	12000 MHz	0.16 Ω	300 mA
L-07C2N4SV6T	2.4 nH	± 0.3 nH	8	100 MHz	10000 MHz	0.16 Ω	300 mA
L-07C2N7SV6T	2.7 nH	± 0.3 nH	8	100 MHz	9500 MHz	0.17 Ω	300 mA
L-07C3N0@V6T	3.0 nH	± 0.3 nH	8	100 MHz	9000 MHz	0.18 Ω	300 mA
L-07C3N3@V6T	3.3 nH	± 0.3 nH ±10%	8	100 MHz	8500 MHz	0.19 Ω	300 mA
L-07C3N6@V6T	3.6 nH	± 0.3 nH ±10%	8	100 MHz	7500 MHz	0.21 Ω	300 mA
L-07C3N9@V6T	3.9 nH	± 0.3 nH ±10%	8	100 MHz	7000 MHz	0.22 Ω	300 mA
L-07C4N3@V6T	4.3 nH	± 0.3 nH ±10%	8	100 MHz	6000 MHz	0.24 Ω	300 mA

* = Choice of C or S Tolerance, @ = S or K Tolerance, # = J or K Tolerance

0402 CONTINUED

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-07C4N7@V6T	4.7 nH	± 0.3 nH ±10%	8	100 MHz	6000 MHz	0.24 Ω	300 mA
L-07C5N1@V6T	5.1 nH	± 0.3 nH ±10%	8	100 MHz	5500 MHz	0.26 Ω	300 mA
L-07C5N6@V6T	5.6 nH	± 0.3 nH ±10%	8	100 MHz	5400 MHz	0.27 Ω	300 mA
L-07C6N2#V6T	6.2 nH	±5% ±10%	8	100 MHz	5200 MHz	0.30 Ω	300 mA
L-07C6N8#V6T	6.8 nH	±5% ±10%	8	100 MHz	5000 MHz	0.32 Ω	250 mA
L-07C7N5#V6T	7.5 nH	±5% ±10%	8	100 MHz	4600 MHz	0.40 Ω	250 mA
L-07C8N2#V6T	8.2 nH	±5% ±10%	8	100 MHz	4600 MHz	0.40 Ω	250 mA
L-07C10N#V6T	10.0 nH	±5% ±10%	8	100 MHz	3700 MHz	0.45 Ω	250 mA
L-07C12N#V6T	12.0 nH	±5% ±10%	8	100 MHz	3200 MHz	0.50 Ω	250 mA
L-07C13N#V6T	13.0 nH	±5% ±10%	8	100 MHz	3100 MHz	0.55 Ω	250 mA
L-07C15N#V6T	15.0 nH	±5% ±10%	8	100 MHz	3100 MHz	0.60 Ω	250 mA
L-07C18N#V6T	18.0 nH	±5% ±10%	8	100 MHz	2900 MHz	0.65 Ω	200 mA
L-07C20N#V6T	20.0 nH	±5% ±10%	8	100 MHz	2100 MHz	0.80 Ω	200 mA
L-07C22N#V6T	22.0 nH	±5% ±10%	8	100 MHz	2100 MHz	0.80 Ω	200 mA
L-07C23N#V6T	23.0 nH	±5% ±10%	8	100 MHz	2100 MHz	0.85 Ω	200 mA
L-07C27N#V6T	27.0 nH	±5% ±10%	8	100 MHz	1900 MHz	0.90 Ω	200 mA
L-07C33N#V6T	33.0 nH	±5% ±10%	8	100 MHz	1600 MHz	1.00 Ω	200 mA
L-07C39N#V6T	39.0 nH	±5% ±10%	8	100 MHz	1400 MHz	1.20 Ω	150 mA
L-07C43N#V6T	43.0 nH	±5% ±10%	8	100 MHz	1300 MHz	1.30 Ω	150 mA
L-07C47N#V6T	47.0 nH	±5% ±10%	8	100 MHz	1200 MHz	1.30 Ω	150 mA
L-07C56N#V6T	56.0 nH	±5% ±10%	8	100 MHz	1100 MHz	2.00 Ω	150 mA
L-07C68N#V6T	68.0 nH	±5% ±10%	8	100 MHz	1000 MHz	2.20 Ω	100 mA
L-07C82N#V6T	82.0 nH	±5% ±10%	8	100 MHz	900 MHz	2.50 Ω	100 mA
L-07CR10#V6T	100 nH	±5% ±10%	8	100 MHz	850 MHz	2.50 Ω	100 mA
L-07CR12#V6T	120 nH	±5% ±10%	8	50 MHz	750 MHz	2.50 Ω	100 mA

0603 INDUCTANCE RANGE / ELECTRICAL CHARACTERISTICS

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-14C1N0SV4E	1.0 nH	± 0.3 nH	8	100 MHz	>17000 MHz	0.10 Ω	300 mA
L-14C1N2SV4E	1.2 nH	± 0.3 nH	8	100 MHz	>17000 MHz	0.10 Ω	300 mA
L-14C1N5SV4E	1.5 nH	± 0.3 nH	8	100 MHz	>17000 MHz	0.10 Ω	300 mA
L-14C1N8SV4E	1.8 nH	± 0.3 nH	8	100 MHz	13000 MHz	0.10 Ω	300 mA
L-14C2N2SV4E	2.2 nH	± 0.3 nH	8	100 MHz	12000 MHz	0.15 Ω	300 mA
L-14C2N7SV4E	2.7 nH	± 0.3 nH	8	100 MHz	8600 MHz	0.15 Ω	300 mA
L-14C3N3@V4E	3.3 nH	± 0.3 nH ±10%	8	100 MHz	6500 MHz	0.20 Ω	300 mA
L-14C3N9@V4E	3.9 nH	± 0.3 nH ±10%	8	100 MHz	6300 MHz	0.20 Ω	300 mA
L-14C4N7@V4E	4.7 nH	± 0.3 nH ±10%	8	100 MHz	5400 MHz	0.20 Ω	300 mA
L-14C5N6@V4E	5.6 nH	± 0.3 nH ±10%	8	100 MHz	4600 MHz	0.25 Ω	300 mA
L-14C6N8#V4E	6.8 nH	±5% ±10%	8	100 MHz	4500 MHz	0.30 Ω	300 mA
L-14C8N2#V4E	8.2 nH	±5% ±10%	8	100 MHz	3800 MHz	0.33 Ω	300 mA
L-14C10N#V4E	10.0 nH	±5% ±10%	8	100 MHz	3700 MHz	0.35 Ω	300 mA
L-14C12N#V4E	12.0 nH	±5% ±10%	8	100 MHz	3200 MHz	0.40 Ω	300 mA
L-14C15N#V4E	15.0 nH	±5% ±10%	8	100 MHz	2900 MHz	0.45 Ω	300 mA
L-14C18N#V4E	18.0 nH	±5% ±10%	10	100 MHz	2100 MHz	0.50 Ω	300 mA
L-14C22N#V4E	22.0 nH	±5% ±10%	10	100 MHz	2100 MHz	0.55 Ω	300 mA
L-14C27N#V4E	27.0 nH	±5% ±10%	10	100 MHz	2000 MHz	0.60 Ω	300 mA
L-14C33N#V4E	33.0 nH	±5% ±10%	10	100 MHz	1600 MHz	0.65 Ω	300 mA
L-14C39N#V4E	39.0 nH	±5% ±10%	10	100 MHz	1500 MHz	0.70 Ω	300 mA
L-14C47N#V4E	47.0 nH	±5% ±10%	12	100 MHz	1200 MHz	0.90 Ω	300 mA
L-14C56N#V4E	56.0 nH	±5% ±10%	12	100 MHz	1100 MHz	1.00 Ω	300 mA
L-14C68N#V4E	68.0 nH	±5% ±10%	12	100 MHz	1000 MHz	1.10 Ω	300 mA
L-14C82N#V4E	82.0 nH	±5% ±10%	12	100 MHz	850 MHz	1.20 Ω	300 mA
L-14CR10#V4E	100 nH	±5% ±10%	12	100 MHz	750 MHz	1.20 Ω	300 mA
L-14CR12#V4E	120 nH	±5% ±10%	8	50 MHz	700 MHz	1.30 Ω	300 mA
L-14CR15#V4E	150 nH	±5% ±10%	8	50 MHz	650 MHz	1.40 Ω	300 mA
L-14CR18#V4E	180 nH	±5% ±10%	8	50 MHz	550 MHz	1.50 Ω	300 mA
L-14CR22#V4E	220 nH	±5% ±10%	8	50 MHz	450 MHz	1.70 Ω	300 mA







@ = Choice of S or K Tolerance, # = J or K Tolerance

0805 INDUCTANCE RANGE / ELECTRICAL CHARACTERISTICS

Part Number	Inductance	Tolerance	Q (Min.)	L/Q Freq.	Typical SRF	DC Resistance Max	Rated Current
L-15C1N5SV4E	1.5 nH	± 0.3 nH	10	100 MHz	>6000 MHz	0.10 Ω	300 mA
L-15C1N8SV4E	1.8 nH	± 0.3 nH	10	100 MHz	>6000 MHz	0.10 Ω	300 mA
L-15C2N2SV4E	2.2 nH	± 0.3 nH	10	100 MHz	>6000 MHz	0.10 Ω	300 mA
L-15C2N7SV4E	2.7 nH	± 0.3 nH	12	100 MHz	>6000 MHz	0.12 Ω	300 mA
L-15C3N3@V4E	3.3 nH	± 0.3 nH ±10%	12	100 MHz	>6000 MHz	0.13 Ω	300 mA
L-15C3N9@V4E	3.9 nH	± 0.3 nH ±10%	12	100 MHz	5600 MHz	0.15 Ω	300 mA
L-15C4N7@V4E	4.7 nH	± 0.3 nH ±10%	12	100 MHz	5500 MHz	0.20 Ω	300 mA
L-15C5N6@V4E	5.6 nH	± 0.3 nH ±10%	12	100 MHz	4700 MHz	0.23 Ω	300 mA
L-15C6N8#V4E	6.8 nH	±5% ±10%	15	100 MHz	3900 MHz	0.25 Ω	300 mA
L-15C8N2#V4E	8.2 nH	±5% ±10%	15	100 MHz	3200 MHz	0.28 Ω	300 mA
L-15C10N#V4E	10.0 nH	±5% ±10%	15	100 MHz	3100 MHz	0.30 Ω	300 mA
L-15C12N#V4E	12.0 nH	±5% ±10%	15	100 MHz	2800 MHz	0.35 Ω	300 mA
L-15C15N#V4E	15.0 nH	±5% ±10%	15	100 MHz	2400 MHz	0.40 Ω	300 mA
L-15C18N#V4E	18.0 nH	±5% ±10%	15	100 MHz	2100 MHz	0.45 Ω	300 mA
L-15C22N#V4E	22.0 nH	±5% ±10%	15	100 MHz	2000 MHz	0.50 Ω	300 mA
L-15C27N#V4E	27.0 nH	±5% ±10%	15	100 MHz	1800 MHz	0.55 Ω	300 mA
L-15C33N#V4E	33.0 nH	±5% ±10%	15	100 MHz	1700 MHz	0.60 Ω	300 mA
L-15C39N#V4E	39.0 nH	±5% ±10%	18	100 MHz	1400 MHz	0.65 Ω	300 mA
L-15C47N#V4E	47.0 nH	±5% ±10%	18	100 MHz	1200 MHz	0.70 Ω	300 mA
L-15C56N#V4E	56.0 nH	±5% ±10%	18	100 MHz	1000 MHz	0.75 Ω	300 mA
L-15C68N#V4E	68.0 nH	±5% ±10%	18	100 MHz	900 MHz	0.80 Ω	300 mA
L-15C82N#V4E	82.0 nH	±5% ±10%	18	100 MHz	900 MHz	0.85 Ω	300 mA
L-15CR10#V4E	100 nH	±5% ±10%	18	100 MHz	700 MHz	0.90 Ω	300 mA
L-15CR12#V4E	120 nH	±5% ±10%	13	50 MHz	600 MHz	0.95 Ω	300 mA
L-15CR15#V4E	150 nH	±5% ±10%	13	50 MHz	500 MHz	1.00 Ω	300 mA
L-15CR18#V4E	180 nH	±5% ±10%	13	50 MHz	430 MHz	1.10 Ω	300 mA
L-15CR22#V4E	220 nH	±5% ±10%	12	50 MHz	400 MHz	1.20 Ω	300 mA
L-15CR27#V4E	270 nH	±5% ±10%	12	50 MHz	340 MHz	1.30 Ω	300 mA
L-15CR33#V4E	330 nH	±5% ±10%	12	50 MHz	320 MHz	1.50 Ω	300 mA
L-15CR39#V4E	390 nH	±5% ±10%	10	50 MHz	270 MHz	1.60 Ω	300 mA
L-15CR47#V4E	470 nH	±5% ±10%	10	50 MHz	250 MHz	1.80 Ω	300 mA
L-15CR56#V4E	560 nH	±5% ±10%	10	50 MHz	230 MHz	2.50 Ω	300 mA
L-15CR68#V4E	680 nH	±5% ±10%	10	50 MHz	180 MHz	3.00 Ω	300 mA

“@ = Choice of S or K Tolerance, # = J or K Tolerance”

RF CHARACTERISTICS CHARACTERISTICS (TYPICAL)



MECHANICAL & ENVIRONMENTAL CHARACTERISTICS

SPECIFICATION

SOLDERABILITY:	Solder coverage $\geq 75\%$ of electrodes $L = \pm 10\%$ $Q = \pm 20\%$
RESISTANCE TO SOLDERING:	No apparent damage Solder coverage $\geq 75\%$ $L = \pm 10\%$ $Q = \pm 20\%$
THERMAL SHOCK:	No apparent damage $L = \pm 10\%$ $Q = \pm 20\%$
LIFE TEST:	No apparent damage $L = \pm 10\%$ $Q = \pm 20\%$
HUMIDITY RESISTANCE:	Inductance change: 2% or .5pF Max
TERMINAL ADHESION:	Termination should not pull off. Ceramic should remain undamaged.
PCB DEFLECTION:	No mechanical damage.

TEST PARAMETERS

Preheat $120 \pm 20^\circ\text{C}$ for 1 min. Dip $230 \pm 10^\circ\text{C}$ for 3 ± 1 sec.
 Preheat $120 \pm 20^\circ\text{C}$ for 1 min. Dip $260 \pm 10^\circ\text{C}$ for 10 ± 1 sec.
 100 cycles: 30 ± 3 minutes @ $+100^\circ\text{C}$ then 30 ± 3 min. @ -40°C
 1000 ± 48 Hours @ $+85 \pm 2^\circ\text{C}$, rated current (1-2 hour recovery)
 1000 ± 48 Hours @ $+40 \pm 2^\circ\text{C}$, 90-95% relative humidity, rated current (1-2 hour recovery)
 Lateral pull force: 0201 ≥ 1.0 Lbs 0402 ≥ 1.6 Lbs
 For 0603 ≥ 2.2 Lbs For 0805 ≥ 4.4 Lbs
 Glass Epoxy PCB: 1 mm deflection