


## Bulk Metal<sup>®</sup> Foil Technology High Precision Voltage Divider Resistors with TCR Tracking to 0.5 ppm/°C and Tolerance Match to 0.005 % (50 ppm)



### INTRODUCTION

#### Why tight tolerance is important?

Why do users employ tight tolerance resistors? A system or a device or one particular circuit element must perform for a specified period of time and at the end of that service period it must still be performing within specifications.

During its useful life it may have been subjected to some hostile service conditions and it is no longer within purchased tolerance.

#### What is ratio?

The ratio tolerances available in a divider are variable and dependent on resistor technology. Bulk Metal<sup>®</sup> foil provides the tightest ratio tolerance available.

The tight resolution capability and overall stability of foil resistors permit adjustment within the divider to ratio not available with other technologies. Ratios in network form, in a common package have a better chance of holding tight tolerances than those formed in a discrete matched set by sorting.

Molded foil 300144, 300145 resistors can be provided in a tolerance as tight as 0.005 %. Theoretically, ratios such as these can be made initially with other resistor technologies. However, less stable products will not hold these tight ratios tolerances over time and applied stresses like voltage and temperature.

Vishay Bulk Metal foil dividers/networks 300144, 300145 hold their ratio tolerances under defined circumstances. Networks with tight ratio tolerances and controlled tracking extend the useful life of equipment, whether expressed as mean-time-between-failures (MTBF) or service periods to recalibration or end-of-life-cycle.

#### How to avoid thermal EMF?

When the resistor's terminals and the resistive element are made of dissimilar metals and two junctions are at a different temperature, a voltage is produced which is called "thermal EMF".

The level of voltage output is a function of the metals involved and the differential temperature. The voltage produced is either positive or negative depending on which junction is considered as a reference point. Virtually all resistive products have these metallic junctions. It is presumed they will eventually be terminated to copper as a final metallic combination and therefore copper is used as a typical reference material.

300144, 300145 have the lowest thermal EMF's because all junctions have low microvolts outputs. Moreover, construction of the resistive element is such that the input and output junctions of the resistor are so close that the temperature gradients between them is highly unlikely. These design factors produce a divider with very low thermal EMF.

Our application engineering department is available to advise and make recommendations. For non-standard technical requirements and special applications. Please contact us.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

### FEATURES


- Temperature coefficient of resistance (TCR) absolute:  $\pm 2$  ppm/°C typical (- 55 °C to + 125 °C, + 25 °C ref.)  
TCR tracking: 0.5 ppm/°C
- Tolerance: absolute and matching to 0.005 % (50 ppm)
- Power rating: 0.2 W at 70 °C, for the entire resistive element  $R_1$  and  $R_2$ , divided proportionally between the two values
- Load life ratio stability: < 0.005 % (50 ppm) 0.2 W at 70 °C for 2000 h
- Maximum working voltage: 200 V
- Resistance range: 100R to 20K per resistive element
- Vishay Foil resistors are not restricted to standard values/ratios; specific "as requested" values/ratios can be supplied at no extra cost or delivery (e.g. 1K2345 vs. 1K)
- Electrostatic discharge (ESD) up to 25 000 V
- Non-inductive, non-capacitive design
- Rise time: 1 ns effectively no ringing
- Thermal stabilization time < 1 s (nominal value achieved within 10 ppm of steady state value)
- Current noise: 0.010  $\mu V_{RMS}/V$  of applied voltage (< - 40 dB)
- Thermal EMF: 0.05  $\mu V/°C$  typical
- Voltage coefficient: < 0.1 ppm/V
- Non inductive: < 0.08  $\mu H$
- Non hot spot design
- Terminal finish: lead (Pb)-free or tin/lead alloy
- Compliant to RoHS directive 2002/95/EC
- Prototype quantities available in just 5 working days or sooner. For more information, please contact [foil@vishaypg.com](mailto:foil@vishaypg.com)
- For better performances see 300144Z, 300145Z (Z-Foil) datasheet



Available  
**RoHS\***  
COMPLIANT

### APPLICATIONS

- Instrumentation amplifiers
- Bridge networks
- Differential amplifiers
- Military
- Space
- Medical
- Automatic test equipment
- Down-hole (high temperature)



**TABLE 1A - MODELS 300144 AND 300145 SPECIFICATIONS**

RESISTANCE VALUES	ABSOLUTE TOLERANCE	ABSOLUTE TCR (-55 °C to +125 °C, + 25 °C ref.)
		TYPICAL AND MAX. SPREAD
≥ 500 Ω to 20 kΩ	± 0.005 %	± 2 ppm/°C ± 3 ppm/°C
100 Ω to < 500 Ω	± 0.01 %	


**TABLE 1B - MODELS 300144 AND 300145 SPECIFICATIONS**

RESISTANCE RATIO	TOLERANCE MATCH	TCR TRACKING MAX.
1:1	0.005 %	0.5 ppm/°C
> 1:1 to 4:1		1.0 ppm/°C
> 4:1 to 10:1	0.01 %	1.5 ppm/°C
> 10:1		2.0 ppm/°C


**Note**

- See table 3 for additional established ratios


**FIGURE 1 - TRIMMING TO VALUES** (conceptual illustration)



**FIGURE 2 - STANDARD PRINTING AND DIMENSIONS** in inches (millimeters)




**FIGURE 3 - POWER DERATING CURVE  
300144, 300145**




Note: Power is divided proportionally between the 2 values

**FIGURE 4 - TYPICAL RESISTANCE/  
TEMPERATURE CURVE**



**TABLE 2 - GLOBAL PART NUMBER INFORMATION (1)**

NEW GLOBAL PART NUMBER: Y0006V0058QT9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y0006 V0058 Q T 9 L:

TYPE: 300144  
VALUES: 2K/20K  
ABSOLUTE TOLERANCE: ± 0.02 %  
TOLERANCE MATCH: 0.01 %  
TERMINATION: lead (Pb)-free  
PACKAGING: bulk pack

HISTORICAL PART NUMBER: 300144T 2K/20K TCR2 Q T B (will continue to be used)

<b>300144</b>	<b>T</b>	<b>2K/20K</b>	<b>TCR2</b>	<b>Q</b>	<b>T</b>	<b>B</b>
MODEL	TERMINATION	OHMIC VALUE	TCR CHARACTERISTIC	ABSOLUTE TOLERANCE	TOLERANCE MATCH	PACKAGING
<b>300144</b> <b>300145</b>	<b>T</b> = lead (Pb)-free <b>None</b> = tin/lead alloy	<b>R<sub>1</sub></b> = 2 kΩ <b>R<sub>2</sub></b> = 20 kΩ <b>R<sub>3</sub></b> <sup>(2)</sup> <b>R<sub>4</sub></b> <sup>(2)</sup>		<b>V</b> = ± 0.005 % <b>T</b> = ± 0.01 % <b>Q</b> = ± 0.02 % <b>A</b> = ± 0.05 % <b>B</b> = ± 0.1 % <b>D</b> = ± 0.5 % <b>F</b> = ± 1.0 %	<b>V</b> = 0.005 % <b>T</b> = 0.01 % <b>Q</b> = 0.02 % <b>A</b> = 0.05 % <b>B</b> = 0.1 % <b>D</b> = 0.5 % <b>F</b> = 1.0 %	<b>B</b> = bulk pack

**Notes**

- (1) For non-standard requests, please contact application engineering
- (2) For 300145 please specify the resistance value for each resistor even if all values are equal

**TABLE 3 - EXAMPLES OF VCODES FOR POPULAR VALUES** (other values available on request)

300144 RATIOS						300145 RATIOS				
VCODES	R <sub>1</sub>	R <sub>2</sub>	VCODES	R <sub>1</sub>	R <sub>2</sub>	VCODES	R <sub>1</sub>	R <sub>2</sub>	R <sub>3</sub>	R <sub>4</sub>
V0009	20K	20K	V0058	2K	20K	V0008	10K	10K	10K	10K
V0010	20K	10K	V0030	2K	18K	V0019	5K	5K	5K	5K
V0100	20K	2K	V0029	2K	4K	V0092	1K	7K812	7K812	1K
V0055	19K4	9K7	V0059	2K	2K	V0023	500R	500R	500R	500R
V0223	17K5	20K	V0103	2K	3K	V0047	100R	8K8	100R	8K8
V0097	15K	15K	V0154	1K5	3K	V0051	100R	10K	100R	10K
V0001	10K	10K	V0032	1K	16K	V0051	100R	10K	100R	10K
V0042	10K	8K323	V0121	1K	2K	V0227	350R	350R	350R	350R
V0006	10K	2K	V0004	1K	1K	-	-	-	-	-
V0166	10K	15K	V0379	1K	7K	-	-	-	-	-
V0226	9K	10K	V0374	800R	800R	-	-	-	-	-
V0003	9K	1K	V0022	511R	16K2	-	-	-	-	-
V0013	8K	16K	V0091	500R	500R	-	-	-	-	-
V0107	6K	20K	V0162	500R	15K	-	-	-	-	-
V0014	6K	7K	V0378	500R	4K5	-	-	-	-	-
V0160	6K	6K	V0061	300R	300R	-	-	-	-	-
V0159	5K5	7K7	V0088	100R	100R	-	-	-	-	-
V0005	5K	10K	V0380	100R	15K	-	-	-	-	-
V0002	5K	5K	V0375	100R	12K3	-	-	-	-	-
V0373	4K	12K	V0381	100R	50R	-	-	-	-	-
V0026	3K	19K2	V0377	50R	28K	-	-	-	-	-
V0156	3K	6K	V0376	35R	20K	-	-	-	-	-
V0158	2K7	10K	-	-	-	-	-	-	-	-

**Note**

- A combination of these values are available in reverse order and in values up to 5 digits

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.