

TECHNICAL DATA  
DATA SHEET 1232, REV. -

## DC-DC Converters

### Wide Input (2:1), 500V Isolation, Regulated, Dual Output

#### FEATURES:

- Isolation Voltage: 500Vdc
- Isolation Resistance (1): >10MW
- Short-Circuit Duration: Continuous
- Max. Temperature Rise: +85° C
- Cooling Method: Free-Air Cooling
- Operating Temp.: -25° C ~ + 70° C
- Storage Temp.: -40° C ~ + 105° C
- Humidity:  $\leq$  90%
- Soldering Temp. (2): 300° C
- Case Material: Non-Flammable Material (UL94-V0)
- Mean Time Before Failure: > 200,000 hours (Operating Temp. 25° C)

#### W-10W Dual Output Series Input Characteristics

Part Number	Nominal Input Voltage	Input Voltage Range	Maximum Input Voltage*
W12XXGD10	12Vdc	9~18Vdc	22Vdc
W24XXGD10	24Vdc	18~36Vdc	40Vdc
W48XXGD10	48Vdc	36~72Vdc	80Vdc

\* Voltage above this value may cause permanent damage to the device.

#### W-10W Dual Output Series Output Characteristics

Parameter	MIN	TYP	MAX	Units
Output Power	-	-	10	W
Output Voltage Accuracy	-	$\pm 1$	$\pm 3$	%
Load Regulation	-		$\pm 0.5$	%
Temperature Coefficient	-		$\pm 0.02$	%/°C
Ripple & Noise	50	-	100	mVp-p
Switching Frequency at 100% Load	-	-	300	kHz

1. All specifications at TA=25°C, 75% of the humidity, Nominal input voltage, full output load unless otherwise specified.
2. Soldering for 10 seconds at 1.5mm away from the edge.


**TECHNICAL DATA**  
**DATA SHEET 1232, REV. -**

**W-10W Dual Output Series Part Number List**

Input	Output	Power	Ripple & Noise	Efficiency	Dual-10W
12Vdc	± 5V/100mA ± 12V/42mA ± 15V/34mA	10W	50 mVp-p	80 %	W1205GD10
			100 mVp-p	82 %	W1212GD10
			100 mVp-p	82 %	W1215GD10
24Vdc			50 mVp-p	80 %	W2405GD10
			100 mVp-p	83 %	W2412GD10
			100 mVp-p	83 %	W2415GD10
48Vdc			50 mVp-p	84 %	W4805GD10
			100 mVp-p	86 %	W4812GD10
			100 mVp-p	86 %	W4815GD10

**Mechanical Dimensions: in inch (mm)**

**WxxyyGD10 PACKAGE DIMENSIONS**



**PIN CONFIGURATION**

Pin	Function
	WxxyyGD10
1	+Vin
2	-Vin
3	-Vout
4	COM
5	+Vout

**TECHNICAL DATA**

**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.