



Fxx*1)S1Gy*2)-1423

e.g. F15S1G1-1423

*1) xx No. of contacts 09, 15, 25 or 37
 *2) y for performance classes 1, 2 or 3
 (contact cycle for G1/G2/G3 = 500/200/50)

xx	A (mm)	B (mm)	C (mm)	*øE (mm)
09	30,8	16,4	25	ø 1
15	39,1	24,7	33,3	
25	53	38,5	47,04	
37	69,3	54,9	63,5	

*PCB hole patterns, øE on supplement AM0023

4	2	Through hole spacer	D3,1 / Steel	tin plated
3	xx	Signal contact	S1 / Brass	G1/G2/G3
2	1	Shell	Steel	tin plated
1	1	Insulator	PBT (-55°C - +125°C)	white
No.	St.	Part	Type Description/Material	Surface plating/Colour/Class

		Measurement without tolerance acc. to ISO 2768-m		SCALE	TITLE
				2:1	D-Sub Miniature Connector
		NAME / DATE			
		DRAWN			
		CHECKED			
		fctgroup.com		DWG.NO.	REV.
				FxxS1Gy-1423	1
1					
REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:	PAGES 1

COMMENT: ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT, IT IS NOT PERMITTED TO REPRODUCE, COPY, TRANSMIT OR OTHERWISE DISSEMINATE THIS DRAWING OR ITS CONTENTS. IT IS ALSO NOT TO BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.