



PCB Hole Layout

- Material:
- 1.Housing: Polyester, UL94V-0.
 - 2.Terminal: Copper alloy. Gold-plated.

- Electrical:
- 1.Current rating: 1 Amp.
 2. Insulator resistance: 1000MΩ Min.
 - 3.Contact resistance: 20mΩ Max.
 - 4.Dielectric withstanding: AC 500V.
 5. Temperature: -40°C ~ +105°C
- Available pins: 02~50 contacts.

REV.	DESCRIPTION	DATE

<p>TOLERANCE</p> <p>X ±.XX</p> <p>XX ±.XX</p> <p>XXX ±.XX</p>		<p>DRAWER</p> <p><i>Qian Qian Guo</i></p>	
<p>UNITS : mm</p>		<p>CHECK</p> <p><i>Shi Jiong Guo</i></p>	
		<p>DESIGNED</p> <p><i>Qian Qian Guo</i></p>	
<p>SCALE</p> <p>FREE</p>		<p>APPROVAL</p> <p><i>Shao Feng Guo</i></p>	
<p>DATE</p> <p>12 / 10 / 2010</p>		<p>NAME</p> <p>1.27mm Female Header H:4.3 W:2.2 180°</p>	
<p>SIZE</p> <p>A4</p>		<p>PART NO.</p> <p>F1270-H43-SDIP-XX</p>	
<p>SHEET</p> <p>1 OF 1</p>		<p>DRAW NO.</p> <p>F1270-H43-SDIP</p>	
<p>REV.</p> <p>A</p>		<p>REV.</p> <p> </p>	

SynLight 日亮電子科技有限公司
Sun-light Electronic Technologies Inc.