



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM	/	/	/	1E	1D	1C	1DP	2E	2D	2C	2DP	3E	3D	3C	3DP	4E	4D	4C	4B
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	4A	4F	4G	3B	3A	3F	3G	∅	2B	2A	2F	2G	/	1B	1A	1F	1G	Δ	/	COM

NOTE

- 1: TOLERANCES UNLESS OTHERWISE SPECIFIED:  $\pm 0.20$
- 2: VIEWING ANGLE: 6 O'CLOCK
- 3: POLARIZER: REFLECTIVE
- 4: DUTY: STATIC
- 5: DRIVING VOLTAGE: 3V
- 6: OPERATING TEMPERATURE: 0°C TO 50°C
- 7: STORAGE TEMPERATURE: -20°C TO 70°C

AZ Displays, Inc.		
DRAWN BY: H. D. Q	TITLE: 4 Digit	SCALE: 2:1
CHECKED BY: H. L. P		UNIT: mm
Part No. GD-042AP		SIZE: A4
DATE: APR 25.97	SHEET 1	OF 1