

4-Pin DC Micro Cordset


Specifications

Coupling Nut	Nickel-Plated Brass
Connector	Molded oil-resistant polyurethane body
Contacts	Gold over nickel-plated brass
Cable	Black oil-resistant PVC jacket, 22AWG conductors, 300V
Cable O.D.	4/c = 5mm (0.21in) 5/c = 6.5mm (0.25in)
Temperature	-20°C to +105°C (-4°F to +221°F)

Features

- Ratcheting coupling nut
- Standard black PVC jacket offers good oil and chemical resistance


Dimensions—mm (in)



Straight Female

Dimensions are approximate. Illustrations are not drawn to scale.

Selection Guide



Female Connector (Sensor End)		Cable			Catalog Number
Face View of Female	Connector Style	Wire Color	Wire Rating	Length—m (ft)	
	Straight	1 Brown 2 White 3 Blue 4 Black	22AWG 300V 3A	2 (6.5)	889D-F4BC-2
				5 (16.4)	889D-F4BC-5
				10 (32.8)	889D-F4BC-10
	Straight	1 Brown 2 White 3 Blue 4 Black 5 Grey		2 (6.5)	889D-F5BC-2
				5 (16.4)	889D-F5BC-5
				10 (32.8)	889D-F5BC-10