

ANSALDO**Ansaldo Trasporti s.p.a.
Unita' Semiconduttori**Via N. Lorenzi 8 - I 16152 GENOVA - ITALY
Tel. int. +39/(0)10 6556549 - (0)10 6556488
Fax Int. +39/(0)10 6442510
Tx 270318 ANSUSE I -**FAST RECOVERY DIODE****ARF241**

Repetitive voltage up to	2500 V
Mean forward current	260 A
Surge current	3 kA


FINAL SPECIFICATION

nov 97 - ISSUE : 01


Symbol	Characteristic	Conditions	T _j [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		150	2500	V
V _{RSM}	Non-repetitive peak reverse voltage		150	2600	V
I _{RRM}	Repetitive peak reverse current	V=VRRM	150	50	mA
CONDUCTING					
I _{F(AV)}	Mean forward current	180° sin ,50 Hz, Th=55°C, double side cooled		260	A
I _{F(AV)}	Mean forward current	180° square,50 Hz,Th=55°C,double side cooled		265	A
I _{FSM}	Surge forward current	Sine wave, 10 ms	150	3	kA
I ² t	I ² t	reapplied reverse voltage up to 50% VRSM		45 x1E3	A²s
V _{FM}	Forward voltage	Forward current 300 A	150	2.71	V
V _{F(TO)}	Threshold voltage		150	1.75	V
r _F	Forward slope resistance		150	3.20	mohm
SWITCHING					
t _{rr}	Reverse recovery time	I _F = 200 A di/dt = 80 A/μs V _R = 100 V	150	1.4	μs
Q _{rr}	Reverse recovery charge			50	μC
I _{rr}	Peak reverse recovery current			75	A
s	Softness (s-factor), min			0.4	
V _{FR}	Peak forward recovery	di/dt = 400 A/μs			V
MOUNTING					
R _{th(j-h)}	Thermal impedance	Junction to heatsink, double side cooled		95	°C/kW
T _j	Operating junction temperature			-30 / 150	°C
F	Mounting force			4.5 / 5.0	kN
	Mass			55	g
ORDERING INFORMATION : ARF241 S 25					
standard specification <input type="checkbox"/> <input type="checkbox"/> VRRM/100					

DISSIPATION CHARACTERISTICS

SQUARE WAVE





SINE WAVE




SWITCHING CHARACTERISTICS


FORWARD RECOVERY VOLTAGE



REVERSE RECOVERY CHARGE
Tj = 150 °C




REVERSE RECOVERY CURRENT
Tj = 150 °C




$$t_a = I_{rr} / (di/dt) \quad t_b = t_{rr} - t_a$$

$$\text{Softness (s factor)} \quad s = t_b / t_a$$


$$\text{Energy dissipation during recovery } E_r = V_r \cdot (Q_{rr} - I_{rr} \cdot t_a / 2)$$





FORWARD CHARACTERISTIC
T_j = 150 °C



SURGE CHARACTERISTIC
T_j = 150 °C



TRANSIENT THERMAL IMPEDANCE
DOUBLE SIDE COOLED



Dimensions
in mm



All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness < .03 mm and roughness < 2 μm.

In the interest of product improvement ANSALDO reserves the right to change any data given in this data sheet at any time without previous notice.

If not stated otherwise the maximum value of ratings (symbols over shaded background) and characteristics is reported.

Distributed by

