



POSEICO SPA
POwer SEMiconductors Italian COrporation

POSEICO SPA
Via N. Lorenzi 8, 16152 Genova - ITALY
Tel. ++ 39 010 6556234 - Fax ++ 39 010 6557519
Sales Office:
Tel. ++ 39 010 6556775 - Fax ++ 39 010 6442510

RECTIFIER DIODE

AR302

Repetitive voltage up to **800 V**
Mean forward current **1570 A**
Surge current **16 kA**

FINAL SPECIFICATION

ago 02 - ISSUE : 03

Symbol	Characteristic	Conditions	T _j [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		190	800	V
V _{RSM}	Non-repetitive peak reverse voltage		190	900	V
I _{RRM}	Repetitive peak reverse current	V=VRRM	190	50	mA
CONDUCTING					
I _{F(AV)}	Mean forward current	180° sin ,50 Hz, Th=55°C, double side cooled		1570	A
I _{F(AV)}	Mean forward current	180° sin ,50 Hz, Tc=85°C, double side cooled		1680	A
I _{FSM}	Surge forward current	Sine wave, 10 ms without reverse voltage	190	16	kA
I ² t	I ² t			1280 x 1E3	A ² s
V _{FM}	Forward voltage	Forward current = 3000 A	25	1.55	V
V _{F(TO)}	Threshold voltage		190	0.75	V
r _F	Forward slope resistance		190	0.250	mohm
SWITCHING					
t _{rr}	Reverse recovery time				μs
Q _{rr}	Reverse recovery charge		190		μC
I _{rr}	Peak reverse recovery current				A
MOUNTING					
R _{th(j-h)}	Thermal impedance, DC	Junction to heatsink, double side cooled		50	°C/kW
R _{th(c-h)}	Thermal impedance	Case to heatsink, double side cooled		15	°C/kW
T _j	Operating junction temperature			-30 / 190	°C
F	Mounting force			8.0 / 9.0	kN
	Mass			85	g


ORDERING INFORMATION : AR302 S 08

standard specification VRRM/100


DISSIPATION CHARACTERISTICS

SQUARE WAVE

Th [°C]




PF(AV) [W]




DISSIPATION CHARACTERISTICS

SINE WAVE

Th [°C]




PF(AV) [W]




AR302 RECTIFIER DIODE

FINAL SPECIFICATION ago 02 - ISSUE : 03



FORWARD CHARACTERISTIC
 $T_j = 190\text{ }^\circ\text{C}$



SURGE CHARACTERISTIC
 $T_j = 190\text{ }^\circ\text{C}$



TRANSIENT THERMAL IMPEDANCE
 DOUBLE SIDE COOLED



All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness $< .03\text{ }\mu\text{m}$ and roughness $< 2\text{ }\mu\text{m}$.

In the interest of product improvement POSEICO reserves the right to change any data given in this data sheet at any time without previous notice.

If not stated otherwise the maximum value of ratings (symbols over shaded background) and characteristics is reported.

Distributed by

