

MICRO ELECTRONICS

2612G
(AG2612G)
LED BACKLIGHT
FOR LCD DISPLAY


ABSOLUTE MAXIMUM RATINGS

Forward Current	I_F	220mA
Reverse Voltage	V_R	10V
Operating Temperature	T_{opr}	-20 to +70°C
Storage Temperature	T_{stg}	-30 to +80°C


ELECTRO-OPTICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Forward Voltage	V_F	3.8	4.1	4.4	V	$I_F=110\text{mA}$
Reverse Current	I_R			110	μA	$V_R=10\text{V}$
Peak Wavelength	λ_p		565		nm	$I_F=110\text{mA}$
Spectral Line Half Width	$\Delta\lambda$		40		nm	$I_F=110\text{mA}$
Brightness	B	50			cd/m^2	$I_F=110\text{mA}$

MECHANICAL OUTLINE



CIRCUIT DIAGRAM



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5