


BCW60A**NPN EPITAXIAL SILICON TRANSISTOR****GENERAL PURPOSE TRANSISTOR****ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)**

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CB0}	32	V
Collector-Emitter Voltage	V_{CE0}	32	V
Emitter-Base Voltage	V_{EB0}	5	V
Collector Current	I_C	100	mA
Collector Dissipation	P_C	350	mW
Storage Temperature	T_{stg}	150	$^\circ\text{C}$

• Refer to MMBT3904 for graphs

SOT-23



1. Base 2. Emitter 3. Collector

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)

Characteristic	Symbol	Test Condition	Min	Max	Unit
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C = 2.0\text{mA}, I_B = 0$	32		V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E = 1.0\mu\text{A}, I_C = 0$	5		V
Collector Cutoff Current		$V_{CE} = 32\text{V}, V_{BE} = 0$		20	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 4\text{V}, I_C = 0$		20	nA
DC Current Gain	h_{FE}	$V_{CE} = 5\text{V}, I_C = 2.0\text{mA}$	120	220	
		$V_{CE} = 5\text{V}, I_C = 50\text{mA}$	60		
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 50\text{mA}, I_B = 1.25\text{mA}$		0.55	V
		$I_C = 10\text{mA}, I_B = 0.25\text{mA}$		0.35	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 50\text{mA}, I_B = 1.25\text{mA}$	0.7	1.05	V
		$I_C = 50\text{mA}, I_B = 0.25\text{mA}$	0.6	0.85	V
Base-Emitter On Voltage	$V_{BE(on)}$	$V_{CE} = 5\text{V}, I_C = 2.0\text{mA}$	0.55	0.75	V
Current Gain-Bandwidth Product	f_T	$I_C = 10\text{mA}, V_{CE} = 5\text{V}$ $f = 1\text{MHz}$	125		MHz
Output Capacitance	C_{ob}	$V_{CB} = 10\text{V}, I_E = 0$ $f = 1.0\text{MHz}$		4.5	pF
Noise Figure	NF	$I_C = 0.2\text{mA}, V_{CE} = 5\text{V}$ $R_S = 2\text{K}\Omega, f = 1\text{KHz}$		6	dB
Turn On Time	t_{on}	$I_C = 10\text{mA}, I_{B1} = 1\text{mA}$		150	ns
Turn Off Time	t_{off}	$V_{BB} = 3.6\text{V}, I_{B2} = 1\text{mA}$ $R_1 = R_2 = 5\text{K}\Omega, R_L = 990\Omega$		800	ns

Marking

