


**ANSALDO****Ansaldo Trasporti  
s.p.a.**Via N. Lorenzi 8 - I 16152 GENOVA -  
ITALY  
Tel. int. +39/(0)10 6556549 - (0)10  
6556488  
Fax int. +39/(0)10 6442540**FAST RECOVERY DIODE****ARF220**Repetitive voltage up to **1400 V**  
Mean forward current **445 A**  
Surge current **5 kA****FINAL SPECIFICATION**

ott 97 - ISSUE : 02


Symbol	Characteristic	Conditions	T <sub>j</sub> [°C]	Value	Unit
<b>BLOCKING</b>					
V <sub>RRM</sub>	Repetitive peak reverse voltage		125	1400	V
V <sub>RSM</sub>	Non-repetitive peak reverse voltage		125	1500	V
I <sub>RRM</sub>	Repetitive peak reverse current	V=VRRM	125	50	mA
<b>CONDUCTING</b>					
I <sub>F(AV)</sub>	Mean forward current	180° sin ,50 Hz, Th=55°C, double side cooled		445	A
I <sub>F(AV)</sub>	Mean forward current	180° square,50 Hz,Th=55°C,double side cooled		440	A
I <sub>FSM</sub>	Surge forward current	Sine wave, 10 ms reapplied reverse voltage up to 50% VRSM	125	4.5	kA
I <sup>2</sup> t	I <sup>2</sup> t			101 x1E3	A <sup>2</sup> s
V <sub>FM</sub>	Forward voltage	Forward current 300 A	125	1.18	V
V <sub>F(TO)</sub>	Threshold voltage		125	1.00	V
r <sub>F</sub>	Forward slope resistance		125	0.60	mohm
<b>SWITCHING</b>					
t <sub>rr</sub>	Reverse recovery time	I <sub>F</sub> = 200 A di/dt = 40 A/μs VR = 50 V	125	2.5	μs
Q <sub>rr</sub>	Reverse recovery charge			80	μC
I <sub>rr</sub>	Peak reverse recovery current			70	A
s	Softness (s-factor), min			0.4	
V <sub>FR</sub>	Peak forward recovery	di/dt = 400 A/μs			V
<b>MOUNTING</b>					
R <sub>th(j-h)</sub>	Thermal impedance	Junction to heatsink, double side cooled		95	°C/kW
T <sub>j</sub>	Operating junction temperature			-30 / 125	°C
F	Mounting force			4.5 ,5.0	kN
	Mass			55	g
<b>ORDERING INFORMATION : ARF220 S 14</b>					
standard specification <input type="checkbox"/> <input type="checkbox"/> VRRM/100					

DISSIPATION CHARACTERISTICS

SQUARE WAVE





SINE WAVE




## SWITCHING CHARACTERISTICS


FORWARD RECOVERY VOLTAGE



REVERSE RECOVERY CHARGE  
Tj = 125 °C




REVERSE RECOVERY CURRENT  
Tj = 125 °C




$$t_a = I_{rr} / (di/dt) \quad t_b = t_{rr} - t_a$$

$$\text{Softness (s factor)} \quad s = t_b / t_a$$


$$\text{Energy dissipation during recovery} \quad E_r = V_r \cdot (Q_{rr} - I_{rr} \cdot t_a / 2)$$





**FORWARD CHARACTERISTIC**  
T<sub>j</sub> = 125 °C




**SURGE CHARACTERISTIC**  
T<sub>j</sub> = 125 °C



**TRANSIENT THERMAL IMPEDANCE**  
DOUBLE SIDE COOLED



Dimensions in mm



All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness < .03 mm and roughness < 2  $\mu$ m.

In the interest of product improvement ANSALDO reserves the right to change any data given in this data sheet at any time without previous notice.

If not stated otherwise the maximum value of ratings (symbols over

Distributed by

