

SILICON MULTIPLIER VARACTOR DIODE

DESCRIPTION:

The **1N4387** is a High Power Silicon Multiplier Varactor Diode.

MAXIMUM RATINGS

I_o	200 mA
V_R	150 V
P_{DISS}	20 W @ $T_C = 25^\circ C$
T_J	$-65^\circ C$ to $+150^\circ C$
T_{STG}	$-65^\circ C$ to $+175^\circ C$
θ_{JC}	5.0 $^\circ C/W$

PACKAGE STYLE DO-4

SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN.	MAX.	MIN.	MAX.
A		0.405		10.28
b		0.250		6.35
c				
ϕD		0.505		12.82
ϕD_1	0.265	0.424	6.74	10.76
E	0.423	0.438	10.75	11.12
F_1	0.075	0.175	1.91	4.44
J	0.600	0.800	15.24	20.32
ϕM	0.163	0.189	4.15	4.80
N	0.422	0.453	10.72	11.50
N_1		0.078		1.98
S				
ϕT	0.060	0.095	1.53	2.41
ϕW	10-32	UNF-2A	10-32	UNF-2A

1 = Anode
2 = Cathode

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
V_{BR}	$I_R = 10 \mu A$	150			V
C_T	$V_R = 6.0 V$			35	pF
Q	$V_R = 6.0 V$		200		---
f_{in}				150	MHz
$P_{OUT(x3)}$	$P_{IN} = 30 W$			30	W