

Dual & Quad Ultrafast Rectifiers

SSDI Solid State Devices, Inc.
 14849 Firestone Boulevard • La Mirada, CA 90638
 Phone (213)921-9660 • Fax (714)522-7424

25°C Electrical Characteristics Per Leg					Package Style			
IO A	Configuration	V _F V	V _R V	t _{rr} nsec	16 PIN	20 PIN	28 PIN	MILPACK
1	Common Cathode	1.2	150	9	15ROCT-16	15ROCT-20		
1	Dual Uncommitted	1.2	150	9		15RO-20D		
1	Quad Uncommitted	1.2	150	9	15RO-16Q	15RO-20Q		
1	Common Cathode	1.9	1000	70		SDR1MCT-20		
1	Dual Uncommitted	1.9	1000	70		SDR1M-20D		
1	Quad Uncommitted	1.9	1000	70		SDR1M-20Q		
3	Common Cathode	1.2	150	15		15R1CT-20	15R1CT-28	
3	Dual Uncommitted	1.2	150	15		15R1-20D		
3	Quad Uncommitted	1.2	150	15		15R1-20Q		
3	Common Cathode	1.9	1000	70		SDR3MCT-20	SDR3MCT-28	
3	Dual Uncommitted	1.9	1000	70		SDR3M-20D		
3	Quad Uncommitted	1.9	1000	70		SDR3M-20Q		
6	Common Cathode	1.0	200	20			SPD620CT-28*	SPD620CT-3
6	Common Anode	1.0	200	20				SPD620CA-3
6	Doubler	1.0	200	20				SPD620D-3
20	Common Cathode	1.7	500	35			SDR625CT-28*	SDR625CT-3
20	Common Cathode	1.7	700	60			SDR627CT-28*	SDR627CT-3
20	Common Cathode	1.2	200	35			20R4CT-28*	20R4CT-3
40	Common Cathode	1.7	500	35				SDR625QCT-3
40	Common Cathode	1.7	700	60				SDR627QCT-3
40	Common Cathode	1.0	200	35				20R4QCT-3

* Consult the factory for electrical specifications.