


# EN

Metallized Polypropylene Film AC Power Capacitor

series Safety Mechanism, UL810 approved (Failure current 5,000A)



## Specifications

Item	Performance Characteristics
Applicable Standard	JIS C 4908 (1995)
JIS Approved No.	JIS C 4908 No. 382193
UL Approved No.	UL810 FILE No. E86988
Maximum permissible temperature	+70°C (M)
Minimum ambient temperature	-25°C (B)
Voltage Range	200~440VAC
Capacitance Range	0.5~30 μF
Capacitance Tolerance	+10~-5%
Dielectric Loss Tangent	0.12% or less (at 20°C, 50/60Hz 200VAC)
Withstand Voltage	Between Terminals : Rated Voltage (VAC) × 175% 10secs. Between Terminals connected together and case : 2000VAC 60secs.
Insulation Resistance	Between Terminals connected together and case : 1000MΩ or more (at 500VDC)
Encapsulation	Flame-retardant epoxy cased, Resin filled
Current duration class	40D (40,000h)
Safety Mechanism	Included

Please indicate as "EEN" series when applying to UL.

## Drawing

Please refer to page 206.

## Dimensions

Unit : mm


V (Code) Capacitance Code Size	200VAC (2D)				230VAC (F5)				250VAC (2E)				300VAC (2S)				330VAC (P5)				
	A	B	C	Fig	A	B	C	Fig	A	B	C	Fig	A	B	C	Fig	A	B	C	Fig	
1.0	105	37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0	
1.5	155	37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	13.5	27.0	
2.0	205	37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	13.5	27.0		37.0	15.5	29.0	
2.5	255	37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0		37.0	15.5	29.0		37.0	17.5	31.0	
3.0	305	37.0	11.5	25.0		37.0	13.5	27.0		37.0	13.5	27.0		37.0	15.5	29.0	① ④	37.0	17.5	31.0	① ④
3.5	355	37.0	13.5	27.0	① ④	37.0	13.5	27.0	① ④	37.0	13.5	27.0	① ④	37.0	17.5	31.0	⑦	37.0	19.5	33.0	⑦
4.0	405	37.0	13.5	27.0	⑦	37.0	15.5	29.0	⑦	37.0	15.5	29.0	⑦	37.0	19.5	33.0	⑦	37.0	21.5	35.0	
4.5	455	37.0	15.5	29.0		37.0	15.5	29.0		37.0	15.5	29.0		37.0	19.5	33.0		37.0	21.5	35.0	
5.0	505	37.0	15.5	29.0		37.0	17.5	31.0		37.0	17.5	31.0		37.0	21.5	35.0		37.0	24.0	37.0	
6.0	605	37.0	17.5	31.0		37.0	19.5	33.0		37.0	19.5	33.0		37.0	24.0	37.0		48.0	21.5	35.0	
7.0	705	37.0	17.5	31.0		37.0	21.5	35.0		37.0	21.5	35.0		37.0	24.0	37.0		48.0	24.0	38.0	② ⑤
8.0	805	37.0	19.5	33.0		37.0	21.5	35.0		37.0	21.5	35.0		48.0	21.5	35.0	② ⑤	48.0	24.0	38.0	
10.0	106	37.0	21.5	35.0		37.0	24.0	37.0		37.0	24.0	37.0		58.0	26.0	40.0		58.0	26.0	40.0	
12.0	126	37.0	24.0	37.0		48.0	24.0	38.0	② ⑤	48.0	24.0	38.0	② ⑤	58.0	26.0	40.0		58.0	30.0	44.0	③ ⑥
14.0	146	48.0	21.5	35.0		48.0	24.0	38.0		48.0	24.0	38.0		58.0	26.0	40.0	③ ⑥	58.0	30.0	44.0	
15.0	156	48.0	24.0	38.0	② ⑤	58.0	26.0	40.0		58.0	26.0	40.0		58.0	30.0	44.0		58.0	30.0	44.0	
16.0	166	48.0	24.0	38.0		58.0	26.0	40.0		58.0	26.0	40.0		58.0	30.0	44.0					
18.0	186	58.0	26.0	40.0		58.0	26.0	40.0		58.0	26.0	40.0		58.0	30.0	44.0					
20.0	206	58.0	26.0	40.0		58.0	26.0	40.0	③ ⑥	58.0	26.0	40.0	③ ⑥								
22.0	226	58.0	26.0	40.0	③ ⑥	58.0	30.0	44.0		58.0	30.0	44.0									
25.0	256	58.0	26.0	40.0		58.0	30.0	44.0		58.0	30.0	44.0									
30.0	306	58.0	30.0	44.0																	

V (Code) Capacitance Code Size	350VAC (2V)				375VAC (S5)				400VAC (2G)				440VAC (Y5)				
	A	B	C	Fig	A	B	C	Fig	A	B	C	Fig	A	B	C	Fig	
0.5	504	—	—	—		37.0	11.5	25.0		37.0	11.5	25.0		37.0	11.5	25.0	
1.0	105	37.0	11.5	25.0		37.0	11.5	25.0		37.0	13.5	27.0		37.0	13.5	27.0	
1.5	155	37.0	13.5	27.0		37.0	15.5	29.0	① ④	37.0	15.5	29.0	① ④	37.0	17.5	31.0	⑦
2.0	205	37.0	15.5	29.0		37.0	17.5	31.0	⑦	37.0	17.5	31.0	⑦	37.0	19.5	33.0	
2.5	255	37.0	17.5	31.0	① ④	37.0	19.5	33.0		37.0	19.5	33.0		37.0	24.0	37.0	
3.0	305	37.0	19.5	33.0	⑦	37.0	21.5	35.0		37.0	21.5	35.0		37.0	24.0	37.0	
3.5	355	37.0	21.5	35.0		37.0	21.5	35.0		37.0	24.0	37.0		48.0	24.0	38.0	② ⑤
4.0	405	37.0	21.5	35.0		37.0	24.0	37.0		48.0	21.5	35.0		48.0	24.0	38.0	
4.5	455	37.0	24.0	37.0		48.0	21.5	35.0	② ⑤	48.0	24.0	38.0	② ⑤	58.0	26.0	40.0	
5.0	505	37.0	24.0	37.0		48.0	24.0	38.0		48.0	24.0	38.0		58.0	26.0	40.0	
6.0	605	48.0	24.0	38.0	② ⑤	48.0	24.0	38.0		58.0	26.0	40.0		58.0	26.0	40.0	③ ⑥
7.0	705	58.0	26.0	40.0		58.0	26.0	40.0		58.0	26.0	40.0		58.0	30.0	44.0	
8.0	805	58.0	26.0	40.0		58.0	26.0	40.0	③ ⑥	58.0	26.0	40.0	③ ⑥	58.0	30.0	44.0	
9.0	905	58.0	26.0	40.0	③ ⑥	58.0	26.0	40.0		58.0	30.0	44.0					
10.0	106	58.0	26.0	40.0		58.0	30.0	44.0		58.0	30.0	44.0					
12.0	126	58.0	30.0	44.0													


# EH, EN series

■ Drawing


● Tab terminal 2 (Terminal shape : **□**)



● Tab terminal 1 (Terminal shape : **■**)



● Pin terminal (Terminal shape : **W**)



Remarks : 1) Tab terminal product has bracket as standard. It is also available without bracket.  
 2) Dimension of case bottom is expressed by A and B.  
 3) Dimension B of case top shall be ±1.0mm as shown below.

4) In case of pin terminal product, cased dimension A is only 37mm.

■ Dimensions

Case size (mm)			Case size code ( ) for Pin terminal	Lead pitch G (mm)					
A	B	C		Terminal Shape <b>□</b>		Terminal Shape <b>■</b>			
				Terminal 2	Fig	Terminal 1	Fig	Pin terminal	Fig
37.0	11.5	25.0	01	27.0	①	30.0	④	34.2	⑦
37.0	13.5	27.0*	02 (09) *						
37.0	15.5	29.0	03 (27) **						
37.0	17.5	31.0	04 (11) **						
37.0	19.5	33.0	05						
37.0	21.5	35.0	06						
37.0	24.0	37.0	07						
48.0	18.0	30.0	12	37.0	②	40.0	⑤	—	—
48.0	21.5	35.0	13						
48.0	24.0	38.0	14						
58.0	26.0	40.0	15	47.0	③	50.0	⑥	—	—
58.0	30.0	44.0	16						
58.0	34.0	49.0	17						

\* In case of pin terminal product, dimension will be 37.0×13.5×28.0mm. (Code : 09)  
 \*\* In case of pin terminal product, dimension will be 37.0×15.5×29.0mm. (Code : 27)  
 \*\*\* In case of pin terminal product, dimension will be 37.0×17.5×31.0mm. (Code : 11)