


0.5A MINI SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop
- High Current Capability
- High Surge Current Capability
- Designed for Surface Mount Application
- Plastic Material – UL Recognition Flammability Classification 94V-0



MB-S		
Dim	Min	Max
A	4.50	4.90
B	3.80	4.20
C	0.006	0.35
D	—	0.20
E	—	7.0
G	0.70	1.10
H	1.30	1.70
J	2.30	2.70
K	2.30	2.70
L	—	3.00
M	0.50	0.80
All Dimensions in mm		

Mechanical Data


- Case: Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Case
- Weight: 0.22 grams (approx.)
- Mounting Position: Any
- Marking: Type Number

Maximum Ratings and Electrical Characteristics @ $T_A=25^{\circ}\text{C}$ unless otherwise specified


Single Phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

Characteristic	Symbol	B1S	B2S	B4S	B6S	B8S	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	100	200	400	600	800	V
RMS Reverse Voltage	$V_{R(RMS)}$	70	140	280	420	560	V
Average Rectified Output Current @ $T_A = 40^{\circ}\text{C}$	I_o	0.5					A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30					A
I^2t Rating for Fusing ($t < 8.35\text{ms}$)	I^2t	10					A^2s
Forward Voltage per element @ $I_F = 0.5\text{A}$	V_{FM}	1.0					V
Peak Reverse Current @ $T_A = 25^{\circ}\text{C}$ At Rated DC Blocking Voltage @ $T_A = 125^{\circ}\text{C}$	I_{RM}	5.0 500					μA
Typical Junction Capacitance (per leg) (Note 1)	C_j	25					pF
Typical Thermal Resistance (per leg) (Note 2)	$R_{\theta JA}$	85					K/W
Operating and Storage Temperature Range	T_j, T_{STG}	-55 to +150					$^{\circ}\text{C}$


Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
 2. Thermal resistance junction to ambient mounted on PC board with 13mm² copper pads.




T_A , AMBIENT TEMPERATURE (°C)
Fig. 1 Output Current Derating Curve




V_{FR} , INSTANTANEOUS FORWARD VOLTAGE (V)
Fig. 2 Typ Forward Characteristics (per element)



NUMBER OF CYCLES AT 60 Hz
Fig. 3 Max Non-Repetitive Peak Forward Surge Current



V_R , REVERSE VOLTAGE (V)
Fig. 4 Typ Junction Capacitance (per element)



PERCENT OF RATED PEAK REVERSE VOLTAGE (%)
Fig. 5 Typ Reverse Characteristics (per element)


ORDERING INFORMATION

Product No.♦	Package Type	Shipping Quantity
B1S-T3	Mini Bridge SMD	3000/Tape & Reel
B2S-T3	Mini Bridge SMD	3000/Tape & Reel
B4S-T3	Mini Bridge SMD	3000/Tape & Reel
B6S-T3	Mini Bridge SMD	3000/Tape & Reel
B8S-T3	Mini Bridge SMD	3000/Tape & Reel

♦T3 suffix refers to a 13" reel.

Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.

RECOMMENDED FOOTPRINT



Won-Top Electronics Co., Ltd (WTE) has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.

No. 44 Yu Kang North 3rd Road, Chine Chen Dist., Kaohsiung, Taiwan

Phone: 886-7-822-5408 or 886-7-822-5410

Fax: 886-7-822-5417

Email: sales@wontop.com

Internet: <http://www.wontop.com>

We power your everyday.