



Carvic International Ltd.

B40C1500 THRU B500C1500

<p>FEATURES</p> <ul style="list-style-type: none"> ● Plastic material used carried Underwriters laboratory recognition. ● High case Dielectric strength. ● Typical I_r less than $1 \mu A$. ● Exceeds environmental standards of MIL-STD-19500. ● Ideal for printed circuit board. ● High temperature soldering guaranteed: 265°C /10 seconds / .375." , (9.5mm) lead length at 5 lbs., (2.3kg) tension. <p>MECHANICAL DATA</p> <p>Case: Reliable low cost construction utilizing molded plastic technique.</p> <p>Terminals: Leads, solderable per MIL-STD-202, Method 208.</p> <p>Mounting position: Any.</p> <p>Weight: 0.04 ounces, 1.1 grams.</p>	<p style="text-align: center;">VOLTAGE RANGE 90 to 1200 Volts</p> <p style="text-align: center;">CURRENT 1.5 Amperes</p> <p style="text-align: right;">RB-10</p> <div style="text-align: center;"> </div> <p style="text-align: center;">Dimensions in inches and (millimeters)</p>
--	---

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60 Hz, resistive or inductive load 60 Hz.
 For cpacitive load, derate current by 20%.

	B40C1500	B80C1500	B125C1500	B250C1500	B380C1500	B500C1500	UNITS
Maximum Recurrent Peak Reverse Voltage	90	180	350	600	900	1200	VRRM
Maximum RMS Bridge Input Voltage	70	140	280	420	560	700	VRMS
Maximum DC Blocking Voltage	90	180	350	600	900	1000	VDC
Maximum Average Forward Rectified Current 373" (9.5mm) Lead Lengths at TA=25°C	1.5						A(AV)
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)	50						A ² S
I ² t Rating for Fusing (t<.00835ms)	5.0						
Maximum Forward Voltage Drop per Element at 1.0A	1.0						V
Maximum DC Reverse Current, at rated DC Blocking Voltage	10.0 1.0						μA
TA=25°C TA=100°C							
Typical Junction Capacitance per Bridge Element	24.0						pF
Operating Temperature Range ,TA	- 65 To + 125						°C
Storage Temperature Range TSTG	- 65 To + 150						°C

NOTES: 1.-Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

