



**PRODUCT SUMMARY**

$V_{(BR)DSS}$	$R_{DS(ON)}$	$I_D$
-30	45m	-12A



1. GATE
2. DRAIN
3. SOURCE

**ABSOLUTE MAXIMUM RATINGS ( $T_C = 25\text{ }^\circ\text{C}$  Unless Otherwise Noted)**

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		$V_{DS}$	-30	V
Gate-Source Voltage		$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	$I_D$	-12	A
	$T_C = 70\text{ }^\circ\text{C}$		-10	
Pulsed Drain Current <sup>1</sup>		$I_{DM}$	-30	
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	$P_D$	48	W
	$T_C = 70\text{ }^\circ\text{C}$		20	
Operating Junction & Storage Temperature Range		$T_j, T_{stg}$	-55 to 150	$^\circ\text{C}$

**THERMAL RESISTANCE RATINGS**

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		3	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		75	$^\circ\text{C} / \text{W}$

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>Duty cycle  $\leq 1\%$

**ELECTRICAL CHARACTERISTICS ( $T_C = 25\text{ }^\circ\text{C}$ , Unless Otherwise Noted)**

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1	-1.5	-3.0	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$			$\pm 250$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -24V, V_{GS} = 0V$			1	$\mu A$
		$V_{DS} = -20V, V_{GS} = 0V, T_J = 125\text{ }^\circ\text{C}$			10	
On-State Drain Current <sup>1</sup>	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -10V$	-30			A
Drain-Source On-State Resistance <sup>1</sup>	$R_{DS(ON)}$	$V_{GS} = -4.5V, I_D = -10A$		60	75	m
		$V_{GS} = -10V, I_D = -12A$		37	45	
Forward Transconductance <sup>1</sup>	$g_{fs}$	$V_{DS} = -10V, I_D = -12A$		16		S

DYNAMIC						
Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = -15V, f = 1MHz$		530		pF
Output Capacitance	$C_{oss}$			135		
Reverse Transfer Capacitance	$C_{rss}$			70		
Total Gate Charge <sup>2</sup>	$Q_g$	$V_{DS} = 0.5V_{(BR)DSS}, V_{GS} = -10V, I_D = -12A$		10	14	nC
Gate-Source Charge <sup>2</sup>	$Q_{gs}$			2.2		
Gate-Drain Charge <sup>2</sup>	$Q_{gd}$			2		
Turn-On Delay Time <sup>2</sup>	$t_{d(on)}$	$V_{DS} = -15V, R_L = 1 I_D \cong -1A, V_{GS} = -10V, R_{GS} = 6$		5.7		nS
Rise Time <sup>2</sup>	$t_r$			10		
Turn-Off Delay Time <sup>2</sup>	$t_{d(off)}$			18		
Fall Time <sup>2</sup>	$t_f$			5		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ( $T_c = 25^\circ C$ )						
Continuous Current	$I_S$				-12	A
Pulsed Current <sup>3</sup>	$I_{SM}$				-30	
Forward Voltage <sup>1</sup>	$V_{SD}$	$I_F = -1A, V_{GS} = 0V$			-1.2	V
Reverse Recovery Time	$t_{rr}$	$I_F = -5A, dI_F/dt = 100A / \mu S$		15.5		nS
Reverse Recovery Charge	$Q_{rr}$				7.9	

<sup>1</sup>Pulse test : Pulse Width  $\leq 300 \mu sec$ , Duty Cycle  $\leq 2\%$ .







<sup>2</sup>Independent of operating temperature.






<sup>3</sup>Pulse width limited by maximum junction temperature.

**REMARK: THE PRODUCT MARKED WITH "P06P03LDG", DATE CODE or LOT #**

**Orders for parts with Lead-Free plating can be placed using the PXXXXXXXG parts name**

**Typical Characteristics**





**TO-252 (DPAK) MECHANICAL DATA**

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	9.35		10.4	H	0.89		2.03
B	2.2		2.4	I	6.35		6.80
C	0.45		0.6	J	5.2		5.5
D	0.89		1.5	K	0.6		1
E	0.45		0.69	L	0.5		0.9
F	0.03		0.23	M	3.96	4.57	5.18
G	5.2		6.2	N			

