




DO NOT SCALE DRAWING	 www.fciconnect.com	 ISO PROJECTION 5:1	SCALE
TITLE		DIMENSION IN MILLIMETERS A3	DWG SIZE
Terminal 0.64 DuoTwin Male	CATALOG NUMBER	 SHEET 1 of 1	
CATALOG NUMBER --			

THIS DRAWING AND ALL OTHER INFORMATION CONTAINED THEREIN IS PROPRIETARY AND THE PROPERTY OF FCI. This drawing may not be copied, reproduced or disclosed to any third party without the expressed written permission of FCI. © FCI April 1999

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60181011](#)

[Assistant](#)



60181011

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	15A
Current Carrying Capacity at 85°C	10A
Current Carrying Capacity at 100°C	8A
Maximum Insulation (in mm)	1.1 - 1.6
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.22 - 0.5 mm ²
Contact mating force	< 4N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Crimping Tool	65200601/65200602
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60181014](#)

[Assistant](#)



60181014

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	15A
Current Carrying Capacity at 85°C	10A
Current Carrying Capacity at 100°C	8A
Maximum Insulation (in mm)	1.1 - 1.6
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.22 - 0.5 mm ²
Contact mating force	< 3N
Single Wire Seal Compatible	No
Contact unmating force	< 3N
Physical	
Plating	Au 0.8 μ
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Crimping Tool	65200601/65200602
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60181031](#)

[Assistant](#)



60181031

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental Other Features

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	18A
Current Carrying Capacity at 85°C	11A
Current Carrying Capacity at 100°C	9A
Maximum Insulation (in mm)	1.4 - 1.9
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 0.75 mm ²
Contact mating force	< 4N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Crimping Tool	65200603
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60181034](#)

[Assistant](#)



60181034

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	18A
Current Carrying Capacity at 85°C	11A
Current Carrying Capacity at 100°C	9A
Maximum Insulation (in mm)	1.4 - 1.9
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 0.75 mm ²
Contact mating force	< 3N
Single Wire Seal Compatible	No
Contact unmating force	< 3N
Physical	
Plating	Au 0.8 μ
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Crimping Tool	65200603
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60181211](#)

[Assistant](#)



60181211

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	15A
Current Carrying Capacity at 85°C	10A
Current Carrying Capacity at 100°C	8A
Maximum Insulation (in mm)	1.1 - 1.6
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.22 - 0.5 mm ²
Contact mating force	< 4N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60181214](#)

[Assistant](#)



60181214

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	15A
Current Carrying Capacity at 85°C	10A
Current Carrying Capacity at 100°C	8A
Maximum Insulation (in mm)	1.1 - 1.6
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.22 - 0.5 mm ²
Contact mating force	< 3N
Single Wire Seal Compatible	No
Contact unmating force	< 3N
Physical	
Plating	Au 0.8 μ
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60181231](#)

[Assistant](#)



60181231

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	18A
Current Carrying Capacity at 85°C	11A
Current Carrying Capacity at 100°C	9A
Maximum Insulation (in mm)	1.4 - 1.9
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 0.75 mm ²
Contact mating force	< 4N
Single Wire Seal Compatible	No
Contact unmating force	< 4N
Physical	
Plating	Sn
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.

Direct Links ...

- Cross Reference
- RoHS/LF P/N search
- Document & Drawing search
- Application tooling

Services ...

- Contact us
- Distributor list
- Pricing request
- Order samples

Literature ...

- Brochures & catalogs
- Product documentation
- Technical library

[Back > 60181234](#)

[Assistant](#)



60181234

DuoTwin Male 0.64 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	0.64
Family	DuoTwin
Features	Long Auxiliary Steel Spring in CrNi Suitable for Secondary Lock Low Contact Mating Force

Dimensional

Contact Pitch	2.5 mm
---------------	--------

Electrical

Current Carrying Capacity at 23°C	18A
Current Carrying Capacity at 85°C	11A
Current Carrying Capacity at 100°C	9A
Maximum Insulation (in mm)	1.4 - 1.9
Resistance (Contact)	< 3
Mechanical	
Range of Wire Gauge Min - Max	0.5 - 0.75 mm ²
Contact mating force	< 3N
Single Wire Seal Compatible	No
Contact unmating force	< 3N
Physical	
Plating	Au 0.8 μ
Material	CuNiSi/CrNi
Environmental	
IMDS	No
Other Features	
Type	Male
Tradename	DuoTwin
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.