


**Data Sheet**
**Standard**

- B/G
- D/K
- M/N

**Features**

- TV IF filter switchable from B/G, D/K mode to M/N mode
- B/G, D/K mode with Nyquist slope and broad sound shelf for sound carriers at 32,40 MHz and 33,40 MHz
- Reduced group delay predistortion as compared to standard B/G half
- M/N mode with Nyquist slope and sound shelf at 34,40 MHz
- Constant group delay

Plastic package SIP5K




Dimensions in mm, approx. weight 1,0 g

**Terminals**

- Tinned CuFe alloy

**Pin configuration**

- |   |                       |
|---|-----------------------|
| 1 | Input                 |
| 2 | Switching input       |
| 3 | Chip carrier - ground |
| 4 | Output                |
| 5 | Output                |



Type	Ordering code	Marking and package according to	Packing according to
K 7252 M	B39389-K7252-M100	C81157-A1-A15	F81074-V8067-Z000

**Maximum ratings**

Operable temperature range	$T_A$	-25/+85	°C	
Storage temperature range	$T_{slg}$	-40/+85	°C	
DC voltage	$V_{DC}$	12	V	between any terminals
AC voltage	$V_{pp}$	10	V	between any terminals


**SAW Components**
**K 7252 M**
**IF Filter for Intercarrier / Multistandard Applications**
**38,90 MHz**
**Data Sheet**
**Characteristics in B/G, D/K mode (switching pin 2 connected to ground)**

Reference temperature:  $T_A = 25\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$   
 Terminating load impedance:  $Z_L = 2\text{ k}\Omega \parallel 3\text{ pF}$

		min.	typ.	max.	
<b>Insertion attenuation</b>					
	$\alpha$				
Reference level for the following data	37,40 MHz	15,4	16,9	18,4	dB
<b>Relative attenuation</b>					
	$\alpha_{rel}$				
Picture carrier	38,90 MHz	4,6	5,6	6,6	dB
Color carrier	34,47 MHz	0,2	1,2	2,2	dB
Sound carrier	32,40 MHz	17,7	19,2	20,7	dB
	33,40 MHz	16,0	17,5	—	dB
Adjacent picture carrier	30,90 MHz	46,0	58,0	—	dB
	31,90 MHz	38,0	50,0	—	dB
Adjacent sound carrier	40,40 MHz	41,0	50,0	—	dB
	41,40 MHz	40,0	46,0	—	dB
Lower sidelobe	25,00 ... 30,90 MHz	36,0	42,0	—	dB
Upper sidelobe	40,40 ... 45,00 MHz	33,0	39,0	—	dB
<b>Reflected wave signal suppression</b>					
1,3 $\mu$ s ... 6,0 $\mu$ s after main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)		42,0	50,0	—	dB
<b>Feedthrough signal suppression</b>					
1,2 $\mu$ s ... 1,1 $\mu$ s before main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)		—	56,0	—	dB
<b>Group delay predistortion</b>					
(reference frequency 38,90 MHz)					
	$\Delta\tau$				
	36,80 MHz	—	-40	—	ns
	34,47 MHz	—	50	—	ns
<b>Impedance at 37,40 MHz</b>					
	Input: $Z_{IN} = R_{IN} \parallel C_{IN}$	—	1,0 $\parallel$ 17,3	—	k $\Omega$ $\parallel$ pF
	Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$	—	2,7 $\parallel$ 3,4	—	k $\Omega$ $\parallel$ pF
<b>Temperature coefficient of frequency</b>					
	$TC_f$	—	-72	—	ppm/K



**SAW Components**

**K 7252 M**

**IF Filter for Intercarrier / Multistandard Applications**

**38,90 MHz**

**Data Sheet**

**Characteristics in M/N mode (switching pin 2 connected to pin 1)**

Reference temperature:  $T_A = 25\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$   
 Terminating load impedance:  $Z_L = 2\text{ k}\Omega \parallel 3\text{ pF}$

		<b>min.</b>	<b>typ.</b>	<b>max.</b>	
<b>Insertion attenuation</b>					
	$\alpha$				
Reference level for the following data	37,40 MHz	15,5	17,0	18,5	dB
<b>Relative attenuation</b>					
	$\alpha_{rel}$				
Picture carrier	38,90 MHz	4,9	5,9	6,9	dB
Color carrier	35,32 MHz	0,8	1,8	2,8	dB
Sound carrier	34,40 MHz	17,0	18,5	20,0	dB
Adjacent picture carrier	32,90 MHz	40,0	52,0	—	dB
Adjacent sound carrier	40,40 MHz	41,0	49,0	—	dB
Lower sidelobe	25,00 ..... 32,90 MHz	36,0	42,0	—	dB
Upper sidelobe	40,40 ..... 45,00 MHz	31,0	37,0	—	dB
<b>Reflected wave signal suppression</b>					
1,2 $\mu$ s ... 6,0 $\mu$ s after main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)		42,0	52,0	—	dB
<b>Feedthrough signal suppression</b>					
1,2 $\mu$ s ... 1,1 $\mu$ s before main pulse (test pulse 250 ns, carrier frequency 37,40 MHz)		—	50,0	—	dB
<b>Group delay ripple (p-p)</b>					
	$\Delta\tau$	—	50	—	ns
<b>Impedance at 37,40 MHz</b>					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1,1 $\parallel$ 21,0	—	k $\Omega$ $\parallel$ pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	2,7 $\parallel$ 3,4	—	k $\Omega$ $\parallel$ pF
<b>Temperature coefficient of frequency</b>					
	$TC_f$	—	-72	—	ppm/K



SAW Components



K 7252 M

IF Filter for Intercarrier / Multistandard Applications

38,90 MHz

Data Sheet

Frequency response B/G, D/K mode





SAW Components


K 7252 M

IF Filter for Intercarrier / Multistandard Applications


38,90 MHz

Data Sheet

Frequency response B/G, D/K mode



Time domain response B/G, D/K mode





SAW Components



K 7252 M

IF Filter for Intercarrier / Multistandard Applications

38,90 MHz

Data Sheet

Frequency response M/N mode





SAW Components


K 7252 M

IF Filter for Intercarrier / Multistandard Applications


38,90 MHz

Data Sheet

Frequency response M/N mode



Time domain response M/N mode





**SAW Components**

**K 7252 M**

**IF Filter for Intercarrier / Multistandard Applications**

**38,90 MHz**

Data Sheet

**Published by EPCOS AG**

**Surface Acoustic Wave Components Division, OFW E UE**

**P.O. Box 80 17 09, D-81617 München**

© EPCOS AG 1999. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.