PIN RECEPTACLES
With Organic Fibre Plug® Solder Barrier
(see specific contact range on pages 220 - 228)

0337



0337-0-XX-XX-15-XX-10-0
Solder mount in Ø1,68±0,08 PTH.
#15 Contact for Ø0,51-0,81 pins.
Also available on 8mm wide carrier tape: 6,000 parts per 330mm reel.

4280



4280-0-XX-XX-16-XX-10-0
Solder mount in Ø1,7±0,08 PTH.
#16 Contact for Ø0,56-0,86 pins.
Also available on 8mm wide carrier tape: 6,000 parts per 330mm reel.

5280



5280-0-XX-XX-16-XX-40-0
Solder mount in Ø1,7±0,08 PTH.
#16 Contact for Ø0,56-0,86 pins.
Also available on 16mm wide carrier tape: 2,200 parts per 330mm reel.

0332



0332-0-XX-XX-18-XX-10-0
Solder mount in Ø2,01±0,08 PTH.
#18 Contact for Ø0,94-1,09 pins.
Also available on 16mm wide carrier tape: 2,200 parts per 330mm reel.

0479



0479-0-XX-XX-34-XX-10-0
Solder mount in Ø1,96±0,08 PTH.
#34 Contact for Ø0,81-1,17 pins.
Also available on 16mm wide carrier tape: 2,200 parts per 330mm reel.

0375



0375-0-XX-XX-02-XX-10-0
Solder mount in Ø2,21±0,08 PTH.
#02 Contact for Ø1,02-1,27 pins.
Also available on 12mm wide carrier tape: 4,500 parts per 330mm reel.

0353



0353-0-XX-XX-03-XX-10-0
Solder mount in Ø2,69±0,08 PTH.
#03 Contact for Ø1,02-1,52 pins.
Also available on 12mm wide carrier tape: 1,300 parts per 330mm reel.

0384



0384-0-XX-XX-23-XX-10-0
Solder mount in Ø2,67±0,08 PTH.
#23 Contact for Ø1,14-1,65 pins.
Also available on 12mm wide carrier tape: 2,000 parts per 330mm reel.

0376



0376-0-XX-XX-07-XX-10-0
Solder mount in Ø3,38±0,08 PTH.
#07 Contact for Ø1,65-2,08 pins.
Also available on 16mm wide carrier tape: 1,500 parts per 330mm reel.

0321



0321-0-XX-XX-08-XX-10-0
Solder mount in Ø3,66±0,08 PTH.
#08 Contact for Ø2,13-2,59 pins.
Also available on 16mm wide carrier tape: 1,700 parts per 330mm reel.

3435



3435-0-XX-XX-47-XX-04-0
Solder mount in Ø1,17±0,08 PTH.
#47 Contact for Ø0,64-0,91 and 0,64 square pins.

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard
CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT
SOLDER BARRIER:
Organic Fibre Plug®
DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: ±0,13
DIAMETERS: ±0,05
ANGLES: ± 2°

ORDER CODE: XXXX - 0 - XX - XX - XX - XX -XX - 0

BASIC PART #

SPECIFY PACKAGING:
43 Discrete Receptacles
67 Supplied on 330mm Reels

SPECIFY SHELL FINISH:
01 5,08µm TIN/LEAD OVER NICKEL
◇ **80** 5,08µm TIN OVER NICKEL (RoHS)

CONTACT
#02,#07,#08,#15,#16,#18,#23,#34 or #47 CONTACT (DATA ON PAGES 220 - 228)

SPECIFY CONTACT FINISH:
◇ **27** 0,76µm GOLD OVER NICKEL (RoHS)
01 5,08µm TIN/LEAD OVER NICKEL
◇ **80** 5,08µm TIN OVER NICKEL (RoHS)

RoHS 2002/95/EC