


Outline Drawing (Conforms to TO-220)

Dimensions	Inches	Millimeters
A	0.63 Max.	16.0 Max.
B	0.49 Max.	12.5 Max.
C	0.41 Max.	10.5 Max.
D	0.28	7.0
E	0.18	4.5
F	0.15 Max.	3.8 Max.
G	0.142 ± 0.008 Dia.	3.6 ± 0.2 Dia.
H	0.125 ± 0.008	3.2 ± 0.2

Dimensions	Inches	Millimeters
J	0.99	2.54
K	0.10	2.6
L	0.051	1.3
M	0.051	1.3
N	0.039	1.0
P	0.031	0.8
Q	0.020	0.5



#### Description:

A triac is a solid state silicon AC switch which may be gate triggered from an off-state to an on-state for either polarity of applied voltage.

#### Features:

- Glass Passivation
- Excellent Surge Capability
- Selected for Inductive Loads

#### Applications:

- AC Switch
- Heating
- Motor Controls
- Lighting
- Solid State Relay

#### Ordering Information:

Example: Select the complete eight, nine or ten digit part number you desire from the table - i.e. BCR10CM-8 is a 400 Volt, 10 Ampere Triac

Type	V <sub>DRM</sub> Volts	Code	Inductive Load*
BCR10CM	400	-8	L
	600	-12	

\*For inductive load, add L.



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

**BCR10CM**

Triac

10 Amperes/400-600 Volts

**Absolute Maximum Ratings,  $T_a = 25\text{ }^\circ\text{C}$  unless otherwise specified**

Ratings	Symbol	BCR10CM-8	BCR10CM-12	Units
Repetitive Peak Off-state Voltage	$V_{DRM}$	400	600	Volts
Non-repetitive Peak Off-state Voltage	$V_{DSM}$	500	720	Volts
On-state Current, $T_c = 103^\circ\text{C}$ , $T_c = 93^\circ\text{C}$	$I_{T(RMS)}$	10	10	Amperes
Non-repetitive Peak Surge, One Cycle (60 Hz)	$I_{TSM}$	100	100	Amperes
$I^2t$ for Fusing, $t = 8.3\text{ msec}$	$I^2t$	41.6	41.6	$\text{A}^2\text{sec}$
Peak Gate Power Dissipation, 20 $\mu\text{sec}$	$P_{GM}$	5	5	Watts
Average Gate Power Dissipation	$P_{G(avg)}$	0.5	0.5	Watts
Peak Gate Current	$I_{GM}$	2	2	Amperes
Peak Gate Voltage	$V_{GM}$	10	10	Volts
Storage Temperature	$T_{stg}$	-40 to 125	-40 to 125	$^\circ\text{C}$
Operating Temperature	$T_j$	-40 to 125	-40 to 125	$^\circ\text{C}$
Weight	–	2.3	2.3	Grams



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

**BCR10CM**

Triac

10 Amperes/400-600 Volts

**Electrical and Thermal Characteristics,  $T_j = 25\text{ }^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions (Trigger Mode)				BCR10CM			Units
		$V_D$	$R_L$	$R_G$	$T_j$	Min.	Typ.	Max.	
Gate Parameters									
DC Gate Trigger Current									
MT2+ Gate+	I <sub>GT</sub>	6V	6Ω	330Ω	25°C	–	–	30	mA
MT2+ Gate–		6V	6Ω	330Ω	25°C	–	–	30	mA
MT2– Gate–		6V	6Ω	330Ω	25°C	–	–	30	mA
DC Gate Trigger Voltage									
MT2+ Gate+	V <sub>GT</sub>	6V	6Ω	330Ω	25°C	–	–	1.5	Volts
MT2+ Gate–		6V	6Ω	330Ω	25°C	–	–	1.5	Volts
MT2– Gate–		6V	6Ω	330Ω	25°C	–	–	1.5	Volts
DC Gate Non-trigger Voltage									
All	V <sub>GD</sub>	1/2 V <sub>DRM</sub>	–	–	125°C	0.2	–	–	Volts

**BCR10CM**

**Triac**

10 Amperes/400-600 Volts

**Electrical and Thermal Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction-to-case	$R_{th(j-c)}$	–	–	–	1.8	$^\circ\text{C/W}$
Voltage – Blocking State Maximums Repetitive Off-state Current	$I_{DRM}$	$V_{DRM}$ = Maximum Allowable Repetitive Off-state Voltage Rating, Gate Open Circuited, $T_j = 125^\circ\text{C}$	–	–	2	mA
Current – Conducting State Maximums Peak On-state Voltage	$V_{TM}$	$T_C = 25^\circ\text{C}$ , $I_{TM} = 15\text{A}$	–	–	1.5	Volts
Critical Rate-of-rise of Commutating Off-state Voltage (Commutating $dv/dt$ ) ▲ for inductive load (L)	$(dv/dt)_C$	–	–	–	–	$\text{V}/\mu\text{s}$


$\Delta$ Part Number	$V_{DRM}$ (Volts)	Commutating $dv/dt, (dv/dt)_C$ ( $\text{V}/\mu\text{sec}$ )		Test Condition	Commutating Voltage & Current Waveform (Inductive Load)
		Minimum			
BCR10CM-8L	400	10		$T_j = 125^\circ\text{C}$ ,	
BCR10CM-12L	600	10		Rate of Decay On-state Commutating Current $(di/dt)_C = -5\text{A/msec}$ : Peak Off-state Voltage $V_D = 400\text{V}$	

## BCR10CM


### Triac

10 Amperes/400-600 Volts


**MAXIMUM ON-STATE CHARACTERISTICS**




**TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION-TO-CASE)**




**GATE CHARACTERISTICS (I, II, III)**




**MAXIMUM SURGE CURRENT FOLLOWING RATED LOAD CONDITIONS**




**ALLOWABLE CASE TEMPERATURE VS. RMS ON-STATE CURRENT**




**ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT**




**ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT**



**MAXIMUM ON-STATE POWER DISSIPATION**



**GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE (TYPICAL)**




## BCR10CM


### Triac

10 Amperes/400-600 Volts


**GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE (TYPICAL)**




**HOLDING CURRENT VS. JUNCTION TEMPERATURE (TYPICAL)**




**BREAKOVER VOLTAGE VS. JUNCTION TEMPERATURE (TYPICAL)**




**BREAKOVER VOLTAGE VS. RATE OF RISE OF OFF-STATE VOLTAGE (TYPICAL)**




**REPETITIVE PEAK OFF-STATE CURRENT VS. JUNCTION TEMPERATURE (TYPICAL)**



**COMMUTATION CHARACTERISTICS (TYPICAL)**



**GATE TRIGGER CURRENT VS. GATE CURRENT PULSE WIDTH (TYPICAL)**



**GATE TRIGGER CHARACTERISTICS TEST CIRCUITS**

