



Recommended P.C.B Layout(Top Side)
P.C.B Thickness=1.20mm(Tolerance±0.05)

△ SPECIFICATION

Current Rating: 3A AC/DC
 Voltage Rating: 250V AC/DC
 Temperature Range: -25°C~+85°C
 Contact Resistance: 10Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Withstanding Voltage: 800V AC/Minute
 Pin: C2680 H
 Finish: Tin Plated Over Nickel
 △ Insulator: PA66+15%G.F,Natural
 RoHS Compliant

No.	Dim.A	Dim.B
6	8.00	4.00
8	10.00	6.00
10	12.00	8.00
12	14.00	10.00
14	16.00	12.00
16	18.00	14.00
18	20.00	16.00
20	22.00	18.00
22	24.00	20.00
24	26.00	22.00
26	28.00	24.00
28	30.00	26.00
30	32.00	28.00
32	34.00	30.00
34	36.00	32.00
36	38.00	34.00
38	40.00	36.00
40	42.00	38.00

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .XX ±0.25 .XX ±0.20 .XXX ±0.10 .X ±1 .XX ±1
PART No. PHDXXR-H		MEI		
DRAWING No. PHDXXR-H		HYY		
SCALE NONE		REV. B2		
		CHECKED BY HZF		UNIT mm
		DRAWING BY HYY		
		REV. B2		

NO.	REV.	REVISIONS	CHK	DATE
△ B2		Modify Spec.	HZF	03/11/2009
△ B1		Modify SPEC.	HZF	12/16/2008
△ B0		NEW RELEASE	HZF	11/13/2008