

**Wound MKP capacitors
Small dimensions**
Construction

- Dielectric: polypropylene
- Wound capacitor technology with internal series connection for $V_R \geq 1250$ Vdc
- Plastic case (UL 94 V-0)
- Epoxy resin sealing

Features

- High pulse strength
- High contact reliability
- Small dimensions

Typical applications

- TV S-correction
- TV flyback
- Electronic ballast circuits

Terminals

- Parallel wire leads, tinned
- Also available with $(3,2 \pm 0,3)$ mm lead length

Marking


Manufacturer's logo,
lot number, style and type (P6xx),
rated capacitance (coded),
capacitance tolerance (code letter),
rated dc voltage
(ac voltage for 1600 Vdc/700 Vac and
2000 Vdc/1000 Vac),
date of manufacture (coded)

Delivery mode

Bulk


Taped (Ammo pack or reel)

For notes on taping, [refer to chapter "Taping and packing", page 274.](#)



Dimensions in mm


Lead spacing	Diameter d_1	Type
$e \pm 0,4$		
10,0	0,6	B 32 651
15,0	0,8	B 32 652
22,5	0,8	B 32 653
27,5	0,8	B 32 654
37,5	1,0	B 32 656



Overview of available types

Lead spacing	10 mm ¹⁾	15 mm								
Type	B 32 651	B 32 652								
Page	136	137								
1,0 nF										
1,5 nF										
2,2 nF	1250 Vdc 450 Vac									2000 Vdc 700 Vac
3,3 nF										
4,7 nF										
6,8 nF										
10 nF										
15 nF										
22 nF										
33 nF										
47 nF										
68 nF										
0,10 µF										
0,15 µF										
0,22 µF										
0,33 µF										
0,47 µF										
0,68 µF										
1,0 µF										

1) Additional values on request




B 32 651 ...

B 32 656


Overview of available types

Lead spacing	22,5 mm							
Type	B 32 653							
Page	139							
1,0 nF								
1,5 nF								
2,2 nF								
3,3 nF							2000 Vdc 700 Vac	2000 Vdc 1000 Vac
4,7 nF								
6,8 nF						1600 Vdc 500 Vac		
10 nF								
15 nF						1250 Vdc 500 Vac		
22 nF								
33 nF				1000 Vdc 250 Vac	1600 Vdc 500 Vac			
47 nF								
68 nF								
0,10 µF			630 Vdc 250 Vac					
0,15 µF		400 Vdc 200 Vac						
0,22 µF	250 Vdc 160 Vac							
0,33 µF								
0,47 µF								
0,68 µF								
1,0 µF								

1) Additional values on request


Overview of available types

Lead spacing	27,5 mm						37,5 mm					
Type	B 32 654						B 32 656					
Page	141						142					
22 nF												
33 nF												
47 nF												
68 nF												
0,10 µF												
0,15 µF												
0,22 µF												
0,33 µF												
0,47 µF												
0,68 µF												
1,0 µF												
1,5 µF												
2,2 µF												
3,3 µF												
4,7 µF												


B 32 651
Ordering codes and packing units, lead spacing 10 mm

V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
1250 Vdc ²⁾ (450 Vac)	2,2 nF	4,0 × 9,0 × 13,0	B32651-A7222-+***	1000	1700	1000
	3,3 nF	5,0 × 11,0 × 13,0	B32651-A7332-+***	830	1300	1000
	4,7 nF	5,0 × 11,0 × 13,0	B32651-A7472-+***	830	1300	1000
	6,8 nF	6,0 × 12,0 × 13,0	B32651-A7682-+***	680	1100	1000

 Capacitance tolerance: $\pm 10\% \hat{=} K, \pm 5\% \hat{=} J, (\pm 3,5\% \text{ upon request})$


1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g: B32651-A7222-K3

 2) For pulse loads (pulse width $\leq 1000 \mu s$), a peak voltage of 1400 V_p can be permitted.


Ordering codes and packing units, lead spacing 15 mm


V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
250 Vdc (160 Vac)	0,15 μ F	5,0 \times 10,5 \times 18,0	B32652-A3154-****	1170	1300	1000
	0,22 μ F	6,0 \times 11,0 \times 18,0	B32652-A3224-****	960	1100	1000
	0,33 μ F	7,0 \times 12,5 \times 18,0	B32652-A3334-****	830	900	1000
	0,47 μ F	8,5 \times 14,5 \times 18,0	B32652-A3474-****	680	700	500
	0,68 μ F	9,0 \times 17,5 \times 18,0	B32652-A3684-****	640	700	500
400 Vdc (200 Vac)	68 nF	5,0 \times 10,5 \times 18,0	B32652-A4683-****	1170	1300	1000
	0,10 μ F	5,0 \times 10,5 \times 18,0	B32652-A4104-****	1170	1300	1000
	0,15 μ F	6,0 \times 11,0 \times 18,0	B32652-A4154-****	960	1100	1000
	0,22 μ F	7,0 \times 12,5 \times 18,0	B32652-A4224-****	830	900	1000
	0,33 μ F	8,5 \times 14,5 \times 18,0	B32652-A4334-****	680	700	500
	0,47 μ F	9,0 \times 17,5 \times 18,0	B32652-A4474-****	640	700	500
630 Vdc (250 Vac)	33 nF	5,0 \times 10,5 \times 18,0	B32652-A6333-****	1170	1300	1000
	47 nF	5,0 \times 10,5 \times 18,0	B32652-A6473-****	1170	1300	1000
	68 nF	6,0 \times 11,0 \times 18,0	B32652-A6683-****	960	1100	1000
	0,10 μ F	7,0 \times 12,5 \times 18,0	B32652-A6104-****	830	900	1000
	0,15 μ F	8,5 \times 14,5 \times 18,0	B32652-A6154-****	680	700	500
	0,22 μ F	9,0 \times 17,5 \times 18,0	B32652-A6224-****	640	700	500
1000 Vdc (250 Vac)	10 nF	5,0 \times 10,5 \times 18,0	B32652-A0103-****	1170	1300	1000
	15 nF	5,0 \times 10,5 \times 18,0	B32652-A0153-****	1170	1300	1000
	22 nF	5,0 \times 10,5 \times 18,0	B32652-A0223-****	1170	1300	1000
	33 nF	6,0 \times 11,0 \times 18,0	B32652-A0333-****	960	1100	1000
	47 nF	7,0 \times 12,5 \times 18,0	B32652-A0473-****	830	900	1000
	68 nF	8,5 \times 14,5 \times 18,0	B32652-A0683-****	680	700	500
	0,10 μ F	9,0 \times 17,5 \times 18,0	B32652-A0104-****	640	700	500
	1250 Vdc (500 Vac)	6,8 nF	5,0 \times 10,5 \times 18,0	B32652-A7682-****	1170	1300
10 nF		6,0 \times 11,0 \times 18,0	B32652-A7103-****	960	1100	1000
15 nF		7,0 \times 12,5 \times 18,0	B32652-A7153-****	830	900	1000
22 nF		8,5 \times 14,5 \times 18,0	B32652-A7223-****	680	700	500
33 nF		9,0 \times 17,5 \times 18,0	B32652-A7333-****	640	700	500
1600 Vdc (500 Vac)		3,3 nF	5,0 \times 10,5 \times 18,0	B32652-A1332-****	1170	1300
	4,7 nF	6,0 \times 11,0 \times 18,0	B32652-A1472-****	960	1100	1000
	6,8 nF	7,0 \times 12,5 \times 18,0	B32652-A1682-****	830	900	1000
	10 nF	8,5 \times 14,5 \times 18,0	B32652-A1103-****	680	700	500
	15 nF	9,0 \times 17,5 \times 18,0	B32652-A1153-****	640	700	500

1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g: B32652-A3154-K3


B 32 652
Ordering codes and packing units, lead spacing 15 mm

V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
1600 Vdc ²⁾ (700Vac)	2,2 nF	5,0 × 10,5 × 18,0	B32652-J1222-+***	1170	1300	1000
	3,3 nF	6,0 × 11,0 × 18,0	B32652-J1332-+***	960	1100	1000
	4,7 nF	7,0 × 12,5 × 18,0	B32652-J1472-+***	830	900	1000
	6,8 nF	8,5 × 14,5 × 18,0	B32652-J1682-+***	680	700	500
	10 nF	9,0 × 17,5 × 18,0	B32652-J1103-+***	640	700	500
2000 Vdc (700 Vac)	1,0 nF	5,0 × 10,5 × 18,0	B32652-A2102-+***	1170	1300	1000
	1,5 nF	6,0 × 11,0 × 18,0	B32652-A2152-+***	960	1100	1000
	2,2 nF	7,0 × 12,5 × 18,0	B32652-A2222-+***	830	900	1000
	3,3 nF	8,5 × 14,5 × 18,0	B32652-A2332-+***	680	700	500
	4,7 nF	9,0 × 17,5 × 18,0	B32652-A2472-+***	640	700	500

 Capacitance tolerance: $\pm 10\% \hat{=} K, \pm 5\% \hat{=} J, (\pm 3,5\% \text{ upon request})$


1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g: B32652-J1222-K3

2) Additional capacitance ratings upon request


Ordering codes and packing units, lead spacing 22,5 mm


V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
250 Vdc (160 Vac)	0,22 μ F	6,0 × 15,0 × 26,5	B32653-A3224-****	680	700	720
	0,33 μ F	6,0 × 15,0 × 26,5	B32653-A3334-****	680	700	720
	0,47 μ F	7,0 × 16,0 × 26,5	B32653-A3474-****	580	600	630
	0,68 μ F	8,5 × 16,5 × 26,5	B32653-A3684-****	480	500	510
	1,0 μ F	10,5 × 16,5 × 26,5	B32653-A3105-****	390	400	540
400 Vdc (200 Vac)	0,15 μ F	6,0 × 15,0 × 26,5	B32653-A4154-****	680	700	720
	0,22 μ F	6,0 × 15,0 × 26,5	B32653-A4224-****	680	700	720
	0,33 μ F	7,0 × 16,0 × 26,5	B32653-A4334-****	580	600	630
	0,47 μ F	8,5 × 16,5 × 26,5	B32653-A4474-****	480	500	510
	0,68 μ F	10,5 × 16,5 × 26,5	B32653-A4684-****	390	400	540
	1,0 μ F	11,0 × 20,5 × 26,5	B32653-A4105-****	370	350	510
630 Vdc (250 Vac)	0,10 μ F	6,0 × 15,0 × 26,5	B32653-A6104-****	680	700	720
	0,15 μ F	6,0 × 15,0 × 26,5	B32653-A6154-****	680	700	720
	0,22 μ F	8,5 × 16,5 × 26,5	B32653-A6224-****	480	500	510
	0,33 μ F	10,5 × 16,5 × 26,5	B32653-A6334-****	390	400	540
	0,47 μ F	11,0 × 20,5 × 26,5	B32653-A6474-****	370	350	510
1000 Vdc (250 Vac)	33 nF	6,0 × 15,0 × 26,5	B32653-A0333-****	680	700	720
	47 nF	6,0 × 15,0 × 26,5	B32653-A0473-****	680	700	720
	68 nF	6,0 × 15,0 × 26,5	B32653-A0683-****	680	700	720
	0,10 μ F	8,5 × 16,5 × 26,5	B32653-A0104-****	480	500	510
	0,15 μ F	10,5 × 16,5 × 26,5	B32653-A0154-****	390	400	540
	0,22 μ F	11,0 × 20,5 × 26,5	B32653-A0224-****	370	350	510
	1250 Vdc (500 Vac)	22 nF	6,0 × 15,0 × 26,5	B32653-A7223-****	680	700
33 nF		6,0 × 15,0 × 26,5	B32653-A7333-****	680	700	720
47 nF		8,5 × 16,5 × 26,5	B32653-A7473-****	480	500	510
68 nF		10,5 × 16,5 × 26,5	B32653-A7683-****	390	400	540
0,10 μ F		11,0 × 20,5 × 26,5	B32653-A7104-****	370	350	510
1600 Vdc (500 Vac)		6,8 nF	6,0 × 15,0 × 26,5	B32653-A1682-****	680	700
	10 nF	6,0 × 15,0 × 26,5	B32653-A1103-****	680	700	720
	15 nF	7,0 × 16,0 × 26,5	B32653-A1153-****	580	600	630
	22 nF	8,5 × 16,5 × 26,5	B32653-A1223-****	480	500	510
	33 nF	10,5 × 16,5 × 26,5	B32653-A1333-****	390	400	540
	47 nF	11,0 × 20,5 × 26,5	B32653-A1473-****	370	350	510

1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g.: B32653-A3224-K3



B 32 653

Ordering codes and packing units, lead spacing 22,5 mm

V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
2000 Vdc (700 Vac)	3,3 nF	6,0 × 15,0 × 26,5	B32653-A2332-+***	680	700	720
	4,7 nF	6,0 × 15,0 × 26,5	B32653-A2472-+***	680	700	720
	6,8 nF	8,5 × 16,5 × 26,5	B32653-A2682-+***	480	500	510
	10 nF	10,5 × 16,5 × 26,5	B32653-A2103-+***	390	400	540
	15 nF	11,0 × 20,5 × 26,5	B32653-A2153-+***	370	350	510
2000 Vdc (1000 Vac)	2,2 nF	6,0 × 15,0 × 26,5	B32653-A8222-+***	680	700	720
	3,3 nF	6,0 × 15,0 × 26,5	B32653-A8332-+***	680	700	720
	4,7 nF	8,5 × 16,5 × 26,5	B32653-A8472-+***	480	500	510
	6,8 nF	10,5 × 16,5 × 26,5	B32653-A8682-+***	390	400	540
	10 nF	10,5 × 20,5 × 26,5	B32653-A8103-+***	390	400	540


Capacitance tolerance: $\pm 10\% \hat{=} K$, $\pm 5\% \hat{=} J$, ($\pm 3,5\%$ upon request)

1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g.: B32653-A2332-K3


Ordering codes and packing units, lead spacing 27,5 mm

V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)		
				Ammo pack	Reel	Untaped
250 Vdc (160 Vac)	1,5 μ F	11,0 × 21,0 × 31,5	B32654-A3155-****	–	350	320
	2,2 μ F	12,5 × 21,5 × 31,5	B32654-A3225-****	–	300	280
	3,3 μ F	15,0 × 24,5 × 31,5	B32654-A3335-****	–	–	240
	4,7 μ F	18,0 × 27,5 × 31,5	B32654-A3475-****	–	–	200
400 Vdc (200 Vac)	1,0 μ F	11,0 × 21,0 × 31,5	B32654-A4105-****	–	350	320
	1,5 μ F	12,5 × 21,5 × 31,5	B32654-A4155-****	–	300	280
	2,2 μ F	14,0 × 24,5 × 31,5	B32654-A4225-****	–	–	260
	3,3 μ F	19,0 × 30,0 × 31,5	B32654-A4335-****	–	–	180
630 Vdc (250 Vac)	0,68 μ F	11,0 × 21,0 × 31,5	B32654-A6684-****	–	350	320
	1,0 μ F	13,5 × 23,0 × 31,5	B32654-A6105-****	–	250	260
	1,5 μ F	18,0 × 27,5 × 31,5	B32654-A6155-****	–	–	200
1000 Vdc (250 Vac)	0,22 μ F	11,0 × 21,0 × 31,5	B32654-A0224-****	–	350	320
	0,33 μ F	11,0 × 21,0 × 31,5	B32654-A0334-****	–	350	320
	0,47 μ F	14,0 × 24,5 × 31,5	B32654-A0474-****	–	–	260
	0,68 μ F	18,0 × 27,5 × 31,5	B32654-A0684-****	–	–	200
1250 Vdc (500 Vac)	0,10 μ F	11,0 × 21,0 × 31,5	B32654-A7104-****	–	350	320
	0,15 μ F	11,0 × 21,0 × 31,5	B32654-A7154-****	–	350	320
	0,22 μ F	14,0 × 24,5 × 31,5	B32654-A7224-****	–	–	260
	0,33 μ F	18,0 × 27,5 × 31,5	B32654-A7334-****	–	–	200
1600 Vdc (500 Vac)	47 nF	11,0 × 21,0 × 31,5	B32654-A1473-****	–	350	320
	68 nF	11,0 × 21,0 × 31,5	B32654-A1683-****	–	350	320
	0,10 μ F	14,0 × 24,5 × 31,5	B32654-A1104-****	–	–	260
	0,15 μ F	18,0 × 27,5 × 31,5	B32654-A1154-****	–	–	200
2000 Vdc (700 Vac)	22 nF	11,0 × 21,0 × 31,5	B32654-A2223-****	–	350	320
	33 nF	13,5 × 23,0 × 31,5	B32654-A2333-****	–	250	260
	47 nF	18,0 × 27,5 × 31,5	B32654-A2473-****	–	–	200
	68 nF	19,0 × 30,0 × 31,5	B32654-A2683-****	–	–	180


Capacitance tolerance: $\pm 10\% \hat{=}$ K, $\pm 5\% \hat{=}$ J, ($\pm 3,5\%$ upon request)

1) + Code letter for capacitance tolerance

*** Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.

For capacitors with 3,2 mm lead length, append code number "3" to the tolerance code, e.g.: B32654-A3155-K3


B 32 656
Ordering codes and packing units, lead spacing 37,5 mm

V_R (V_{rms} $f \leq 1$ kHz)	C_R	Maximum dimensions $b \times h \times l$ (mm)	Ordering code ¹⁾	Packing units (pcs)
				Untaped
1000 Vdc (500 Vac)	0,47 μ F	14,0 \times 25,0 \times 42,0	B32656-A474-+***	56
	0,68 μ F	16,0 \times 28,5 \times 42,0	B32656-A684-+***	48
	1,0 μ F	20,0 \times 39,5 \times 42,0	B32656-A105-+***	32
1250 Vdc (500 Vac)	0,22 μ F	14,0 \times 25,0 \times 42,0	B32656-A7224-+***	56
	0,33 μ F	16,0 \times 28,5 \times 42,0	B32656-A7334-+***	48
	0,47 μ F	18,0 \times 32,5 \times 42,0	B32656-A7474-+***	48
	0,68 μ F	20,0 \times 39,5 \times 42,0	B32656-A7684-+***	32
1600 Vdc (600 Vac)	0,10 μ F	12,0 \times 22,0 \times 42,0	B32656-J1104-+***	72
	0,15 μ F	14,0 \times 25,0 \times 42,0	B32656-J1154-+***	56
	0,22 μ F	16,0 \times 28,5 \times 42,0	B32656-J1224-+***	48
2000 Vdc (700 Vac)	0,10 μ F	14,0 \times 25,0 \times 42,0	B32656-J2104-+***	56
	0,15 μ F	18,0 \times 32,5 \times 42,0	B32656-J2154-+***	48
	0,22 μ F	20,0 \times 39,5 \times 42,0	B32656-J2224-+***	32


 Capacitance tolerance: $\pm 10\% \hat{=} K, \pm 5\% \hat{=} J, (\pm 3,5\% \text{ upon request})$

1) + Code letter for capacitance tolerance

For capacitors with 3.2 mm lead length, append code number "3" to the tolerance code, e.g.: B32656-A474-K3

Technical data


Climatic category in accordance with IEC 60068-1	55/100/56			
Lower category temperature T_{\min}	– 55 °C			
Upper category temperature T_{\max}	+ 100 °C			
Damp heat test	56 days/40 °C/93 % relative humidity			
Limit values after damp heat test	Capacitance change $ \Delta C/C $	≤ 3 %		
	Dissipation factor change $\Delta \tan \delta$	≤ 0,5 · 10 ⁻³ (at 1 kHz) ≤ 1,0 · 10 ⁻³ (at 10 kHz)		
	Insulation resistance R_{is} or time constant $\tau = C_R \cdot R_{is}$	≥ 50 % of minimum as-delivered values		
Reliability:				
Reference conditions	0,5 · V_R ; 40 °C			
Failure rate	1 · 10 ⁻⁹ /h = 1 fit			
	For a conversion table for other operating conditions and temperatures, refer to chapter "Quality assurance", page 327.			
Service life	200 000 h			
Failure criteria:				
Total failure	Short circuit or open circuit			
Failure due to variation of parameters	Capacitance change $ \Delta C/C $	> 10 %		
	Dissipation factor $\tan \delta$	> 4 · upper limit values		
	Insulation resistance R_{is}	< 1500 MΩ ($C_R \leq 0,33 \mu\text{F}$)		
	or time constant $\tau = C_R \cdot R_{is}$	< 500 s ($C_R > 0,33 \mu\text{F}$)		
DC test voltage	1,6 · V_R , 2 s			
Category voltage V_C	$T \leq 85 \text{ °C}$	$V_C = 1,0 \cdot V_R$	$V_{C,rms} = 1,0 \cdot V_{rms}$	
Operation with dc voltage or ac voltage V_{rms} up to 1 kHz	$T \leq 100 \text{ °C}$	$V_C = 0,8 \cdot V_R$	$V_{C,rms} = 0,8 \cdot V_{rms}$	
Operating voltage for short operating periods	$T \leq 85 \text{ °C}$	$V = 1,25 \cdot V_C$, max. 2000 h	$V = 1,0 \cdot V_{C,rms}$, max. 2000 h	
	$T \leq 100 \text{ °C}$	$V = 1,25 \cdot V_C$, max. 2000 h	$V = 1,0 \cdot V_{C,rms}$, max. 2000 h	
Dissipation factor $\tan \delta$ (in 10 ⁻³) at 20 °C (upper limit values)		$C_R \leq 0,1 \mu\text{F}$	$0,1 \mu\text{F} < C_R \leq 1 \mu\text{F}$	$C_R > 1 \mu\text{F}$
	at 1 kHz	–	0,5	0,5
	10 kHz	–	0,8	1,5
	100 kHz	5,0	–	–
Insulation resistance R_{is} or time constant $\tau = C_R \cdot R_{is}$ at 20 °C, rel. humidity ≤ 65 % (minimum as-delivered values)	$C_R \leq 0,33 \mu\text{F}$	$C_R > 0,33 \mu\text{F}$		
	100 GΩ	30 000 s		



B 32 651 ...

B 32 656

Impedance Z
versus
frequency f
(typical values)




Pulse handling capability

Maximum permissible voltage change per unit of time for non-sinusoidal voltages (pulse, sawtooth)

V_R	Max. rate of voltage rise V_{pp}/τ in $V/\mu s$ (for $V_{pp} = V_R$)				
	Lead spacing				
	10 mm	15 mm	22,5 mm	27,5 mm	37,5 mm
250 Vdc	–	200	120	50	–
400 Vdc	–	300	150	70	–
630 Vdc	–	350	210	100	–
1000 Vdc	–	400	350	225	90
1250 Vdc	2000	800	750	500	140
1600 Vdc (500 Vac)	–	1500	1000	700	–
1600 Vdc (600 Vac)	–	–	–	–	210
1600 Vdc (700 Vac)	–	1900	–	–	–
2000 Vdc (700 Vac)	–	2200	1400	900	200
2000 Vdc (1000 Vac)	–	–	2000	–	–

For $V_{pp} < V_R$, the permissible voltage rise rate value V_{pp}/τ may be multiplied by the factor V_R/V_{pp} . Also refer to the calculation example in chapter "General technical information", page 302.

V_R	Pulse characteristic k_0 in $V^2/\mu s$ (for $V_{pp} \leq V_R$)				
	Lead spacing				
	10 mm	15 mm	22,5 mm	27,5 mm	37,5 mm
250 Vdc	–	100 000	60 000	25 000	–
400 Vdc	–	240 000	120 000	55 000	–
630 Vdc	–	340 000	255 000	120 000	–
1000 Vdc	–	800 000	675 000	450 000	180 000
1250 Vdc	6 400 000	2 000 000	1 875 000	1 250 000	350 000
1600 Vdc (500 Vac)	–	4 800 000	3 200 000	2 200 000	–
1600 Vdc (600 Vac)	–	–	–	–	672 000
1600 Vdc (700 Vac)	–	6 100 000	–	–	–
2000 Vdc (700 Vac)	–	8 800 000	5 600 000	3 600 000	800 000
2000 Vdc (1000 Vac)	–	–	10 000 000	–	–




B 32 652


Permissible ac voltage V_{rms} versus frequency f

Lead spacing 15 mm


250 Vdc/ 160 Vac




400 Vdc/ 200 Vac




630 Vdc/ 250 Vac



1000 Vdc/ 250 Vac







Permissible ac voltage V_{rms} versus frequency f

Lead spacing 15 mm


1250 Vdc/ 500 Vac




1600 Vdc/ 500 Vac




1600 Vdc/ 700 Vac



2000 Vdc/ 700 Vac






B 32 653


Permissible ac voltage V_{rms} versus frequency f

Lead spacing 22,5 mm


250 Vdc/ 160 Vac




400 Vdc/ 200 Vac




630 Vdc/ 250 Vac



1000 Vdc/ 250 Vac







Permissible ac voltage V_{rms} versus frequency f

Lead spacing 22,5 mm


1250 Vdc/ 500 Vac




1600 Vdc/ 500 Vac




2000 Vdc/ 700 Vac



2000 Vdc/ 1000 Vac






B 32 654


Permissible ac voltage V_{rms} versus frequency f

Lead spacing 27,5 mm


250 Vdc/ 160 Vac




400 Vdc/ 200 Vac




630 Vdc/ 250 Vac



1000 Vdc/ 250 Vac







Permissible ac voltage V_{rms} versus frequency f

Lead spacing 27,5 mm


1250 Vdc/ 500 Vac




1600 Vdc/ 500 Vac



2000 Vdc/ 700 Vac






B 32 656


Permissible ac voltage V_{rms} versus frequency f

Lead spacing 37,5 mm


1000 Vdc/ 500 Vac




1250 Vdc/ 500 Vac




1600 Vdc/ 600 Vac



2000 Vdc/700 Vac






Flyback application

Permissible voltage and current / waveform


Permissible current I_{pp} versus frequency for a duty cycle of 20 % ($t_0/t = 0,2$):



KMK0720-5

Approximation formular for duty cycle higher than 20 %:

$$I'_{pp} = I_{pp} \sqrt{\frac{t_0^3}{t^3}}$$



B 32 651 ...



B 32 656

Flyback application


Permissible current I_{pp} versus rated capacitance C_R


Frequency = 15,75 kHz

Frequency = 31,5 kHz





Frequency = 95 kHz





S-correction application
Permissible voltage and current / waveform





B 32 651 ...



B 32 656

S-correction application


Permissible current I_{pp} versus rated capacitance C_R

Frequency = 15,75 kHz

Frequency = 31,75 kHz



Frequency = 95 kHz



Herausgegeben von EPCOS AG

Marketing Kommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

© EPCOS AG 2000. Alle Rechte vorbehalten. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Mit den Angaben in dieser Broschüre werden die Bauelemente spezifiziert, keine Eigenschaften zugesichert. Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland.

Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Marketing Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2000. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.