

These glass-sealed Zener diodes are suitable for lead mounting on printed circuit boards. They can be used to regulate voltages between 4 and 24 V.


### Features

- available in DO-35 package
- all 1N5000B series diodes have a single black cathode band. In addition, the significant part no. digits and class are marked on the body followed by an R, for instance 1N5230B marking is 5230BR.

### Applications

- voltage regulating

### Dimensions (Units : mm)



### Absolute maximum ratings (T<sub>a</sub>=25°C)

Parameter	Symbol	Limits	Unit
Power dissipation	P <sub>d</sub>	500	mW
Junction temperature	T <sub>j</sub>	175	°C
Storage temperature	T <sub>stg</sub>	-65~ +175	°C

## 1N5000 series Zener diodes

Electrical characteristics (unless otherwise noted,  $T_a = 25^\circ\text{C}$ )

Part no.	Zener voltage subdivision <sup>1</sup>		Operating resistance <sup>2</sup>			Rising operating resistance		Reverse current		Temp coeff $\theta V_z$ (%/°C)
	$V_z$ (V)		$I_z$ (mA)	$Z_z$ ( $\Omega$ ) Max	$I_z$ (mA)	$Z_{zk}$ ( $\Omega$ ) Max	$I_z$ (mA)	$I_R$ ( $\mu\text{A}$ ) Max	$V_R$ (V)	
	Min	Max								
1N5230B	4.47	4.94	20	19	20	1900	0.25	5.0	2.0	$\pm 0.030$
1N5231B	4.85	5.36	20	17	20	1600	0.25	5.0	2.0	$\pm 0.030$
1N5232B	5.32	5.88	20	11	20	1600	0.25	5.0	3.0	+0.038
1N5233B	5.70	6.30	20	7.0	20	1600	0.25	5.0	3.5	+0.038
1N5234B	5.89	6.51	20	7.0	20	1000	0.25	5.0	4.0	+0.045
1N5235B	6.46	7.14	20	5.0	20	750	0.25	3.0	5.0	+0.050
1N5236B	7.13	7.88	20	6.0	20	500	0.25	3.0	6.0	+0.058
1N5237B	7.79	8.61	20	8.0	20	500	0.25	3.0	6.5	+0.062
1N5238B	8.27	9.14	20	8.0	20	600	0.25	3.0	6.5	+0.065
1N5239B	8.65	9.56	20	10	20	600	0.25	3.0	7.0	+0.068
1N5240B	9.50	10.50	20	17	20	600	0.25	2.0	8.0	+0.075
1N5241B	10.45	11.55	20	22	20	600	0.25	2.0	8.4	$\pm 0.076$
1N5242B	11.40	12.60	20	30	20	600	0.25	1.0	9.1	+0.077
1N5243B	12.35	13.65	9.5	13	9.5	600	0.25	0.5	9.9	+0.079
1N5244B	13.30	14.70	9.0	15	9.0	600	0.25	0.1	10.0	+0.082
1N5245B	14.25	15.75	8.5	16	8.5	600	0.25	0.1	11.0	+0.082
1N5246B	15.20	16.80	7.8	17	7.8	600	0.25	0.1	12.0	+0.083
1N5247B	16.15	17.85	7.4	19	7.4	600	0.25	0.1	13.0	+0.084
1N5248B	17.10	18.90	7.0	21	7.0	600	0.25	0.1	14.0	+0.085
1N5249B	18.05	19.95	6.6	23	6.6	600	0.25	0.1	14.0	$\pm 0.086$
1N5250B	19.00	21.00	6.2	25	6.2	600	0.25	0.1	15.0	+0.086
1N5251B	20.90	23.10	5.6	29	5.6	600	0.25	0.1	17.0	+0.087
1N5252B	22.80	25.20	5.2	33	5.2	600	0.25	0.1	18.0	+0.088

<sup>1</sup> The Zener voltage subdivision ( $V_z$ ) is measured in a steady state.

<sup>2</sup> The operating resistance ( $Z_z$  and  $Z_{zk}$ ) is measured by superimposing a minute alternating current in the regulated current ( $I_z$ ).

Electrical characteristic curve




Figure 1