



Coaxial Cable Assemblies and Breakouts

Pomona®



**Pomona
ACCESS**

FAX ON DEMAND This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (909) 469-2991. Enter the Pomona Access number (shown in italics) when prompted.

Coaxial Cable Assemblies and Breakouts


BNC MALE TO UHF MALE, MOLDED STRAIN RELIEF



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90507	1367-C-18	18"	17.85
	1367-C-24	24"	17.85
	1367-C-36	36"	17.85
	1367-C-48	48"	19.15
	1367-C-60	60"	19.15

RATING: 500 VRMS Max., +50°C (+122°F) Max.
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.
BNC/UHF: Body: Brass, Tarnish Resistant Plating
Contact: Gold Plated Brass


UHF MALE WITH MOLDED STRAIN RELIEF



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90821	UHF-C-18	18"	19.95
	UHF-C-24	24"	19.95
	UHF-C-36	36"	19.95
	UHF-C-48	48"	21.00
	UHF-C-60	60"	21.00

RATING: 500 VRMS, +50°C (+122°F) Max.
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.
UHF Connector materials same as Model 1367, left.

BNC MALE TO SMA MALE 50 OHM TEFLON INSULATED CABLE



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90409	4935-BB-24	24"	34.95
	4935-BB-48	48"	34.95
	4935-BB-60	60"	34.95

RATING: 335 VRMS Max., +165°C (+329°F) Max.
CABLE TYPE: RG316/U, .098" O.D.
MATERIAL: SMA: See Model 4846 at right;
BNC: See Model BNC-C (p. 34)


SMA MALE 50 OHM CABLE



<i>Pomona ACCESS</i>	Part No.	Cable Type	Length	PRICE
90398	4846-K-24	50Ω, RG174/U, .100" O.D.	24"	34.35
	4846-K-48	Rating +85°C Max.	48"	34.35
	4846-K-60	Loss: .45 dB/ft. at 1.0GHz Max	60"	34.35
	4846-BB-24	50Ω, RG316/U, .098" O.D.	24"	38.45
	4846-BB-48	Rating +200°C Max.	48"	38.45
	4846-BB-60	Loss: .56 dB/ft. at 3.0GHz Max	60"	38.45
	4846-X-24	50Ω, RG142B/U, .195" O.D.	24"	51.00
	4846-X-48	Double Shield	48"	51.00
	4846-X-60	Rating +200°C Max. Loss: .67 dB/ft. at 12.4GHz Max	60"	51.00

SMA: Body/Fittings: Passivated Stainless Steel
Contact: Gold Plated Brass

SMA MALE TO SMA MALE RIGHT ANGLE - 50 OHM




SMA Connector materials same as 4846, above right.

<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90759	4814-K-24	24"	47.00
	4814-K-48	48"	48.00
	4814-K-60	60"	56.00
	RG 316/U		
	4814-BB-24	24"	53.00
	4814-BB-48	48"	57.00
	4814-BB-60	60"	57.00
	RG 142B/U		
	4814-X-24	24"	56.00
	4814-X-48	48"	68.00
	4814-X-60	60"	68.00

See chart on page 32 for additional cable specifications.

SMA MALE RIGHT ANGLE 50 OHM CABLE



SMA Connector materials same as 4846 above.

<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90758	4813-K-24	24"	50.00
	4813-K-48	48"	53.00
	4813-K-60	60"	53.00
	RG 316/U		
	4813-BB-24	24"	54.00
	4813-BB-48	48"	59.00
	4813-BB-60	60"	59.00
	RG 142B/U		
	4813-X-24	24"	68.00
	4813-X-48	48"	82.00
	4813-X-60	60"	82.00

See chart on page 32 for additional cable specifications.

SMA MALE TO SMA FEMALE



<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90757	4528-K-24	24"	38.70
	4528-K-48	48"	41.00
	4528-K-60	60"	41.00
	RG 316/U		
	4528-BB-24	24"	41.00
	4528-BB-48	48"	47.00
	4528-BB-60	60"	47.00
	RG 142B/U		
	4528-X-24	24"	47.00
	4528-X-48	48"	64.00
	4528-X-60	60"	64.00

SMA material same as Model 4846 above right, except SMA (F): Beryllium Copper center contact

See chart on page 32 for additional cable specifications.

SMA MALE TO TYPE 'N' MALE 50 OHM CABLE



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90395	5058-X-12	12"	42.00
	5058-X-24	24"	42.00
	5058-X-36	36"	42.00
	5058-X-48	48"	57.00
	5058-X-60	60"	57.00

RATING: +200°C (+392°F) Max.
CABLE TYPE: 50Ω, RG142B/U, .195" O.D.
SMA MATERIAL: See Model 4846 above.
Type 'N' MATERIAL: See Model 2256 (p. 36).

See chart on page 32 for additional cable specifications.

Pomona Electronics

Sales: (909) 469-2900 FAX: (909) 629-3317 Tech. Support: (800) 241-2060
© 2001 Pomona Electronics. Specifications and prices subject to change without notice. Printed in U.S.A.

www.pomonaelectronics.com