


EAC Micro Style QD Cordsets



4-Pin EAC Micro Cordset


Specifications

| | |
|---------------------|--|
| Coupling Nut | Epoxy coated zinc |
| Connector | Molded oil-resistant polyurethane body |
| Contacts | Gold over nickel-plated brass |
| Cable | Yellow oil-resistant PVC jacket, 22AWG conductors, 300V, UL recognized and CSA certified |
| Cable O.D. | 5mm (0.21in) |
| Temperature | -20°C to +105°C (-4°F to +221°F) |


Features

- UL recognized and CSA certified
- Ratcheting coupling nut
- Highly visible yellow PVC jacket offers good oil and chemical resistance

Dimensions—mm (in)




Straight Female



Right Angle Female

Selection Guide



Dimensions are approximate. Illustrations are not drawn to scale.

| Female Connector (Sensor End) | | Cable | | | Catalog Number |
|-------------------------------|-----------------|---|---------------------|---------------|----------------|
| Face View of Female | Connector Style | Wire Color | Wire Rating | Length—m (ft) | |
| | Straight | 1 Black 2 Blue 3 Not Used 4 Green/Yellow | 22AWG 300V 3A | 2 (6.5) | 889B-F4AC-2 |
| | | | | 5 (16.4) | 889B-F4AC-5 |
| | | | | 10 (32.8) | 889B-F4AC-10 |
| | Right Angle | | | 2 (6.5) | 889B-R4AC-2 |
| | | | | 5 (16.4) | 889B-R4AC-5 |
| | | | | 10 (32.8) | 889B-R4AC-10 |