




# Coaxial Cable Assemblies and Breakouts

# Pomona®



Cable length is measured from the inside edges of the connectors.  
All dimensions are in inches unless otherwise noted.

Coaxial Cable Assemblies and Breakouts

## BNC MALE 50 OHM CABLE • FIELD SERVICEABLE CONNECTOR

Pomona ACCESS 90445



RATING: 500 VRMS Max., +80°C (+176°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC: Body: Brass, Tarnish Resistant Plating  
Dielectric: PTFE  
Center Contact: Gold Plated Brass

Part No.	Length	PRICE
BNC-C-6	6"	13.45
BNC-C-12	12"	13.45
BNC-C-18	18"	13.45
BNC-C-24	24"	13.45
BNC-C-36	36"	13.45
BNC-C-48	48"	15.25
BNC-C-60	60"	15.25
BNC-C-72	72"	16.35
BNC-C-96	96"	17.55
BNC-C-120	120"	18.75
BNC-C-144	144"	19.95
BNC-C-180	180"	21.75
BNC-C-240	240"	24.75
BNC-C-300	300"	27.75
BNC-C-360	360"	30.25
BNC-C-600	600"	42.75

## BNC MALE 50 OHM CABLE

Pomona ACCESS 90648



RATING: 500 VRMS Max., +80°C (+176°F) Max.  
CABLE TYPE: 50Ω, RG58 type .195" O.D.  
BNC Connector materials same as Model 2249-C (p. 33).

Part No.	Length	PRICE
5697-6	6"	6.30
5697-12	12"	6.30
5697-18	18"	6.30
5697-24	24"	6.30
5697-36	36"	6.30
5697-48	48"	9.15
5697-60	60"	9.15
5697-72	72"	9.15
5697-96	96"	9.15
5697-120	120"	11.05
5697-144	144"	12.00
5697-180	180"	13.45
5697-240	240"	15.85
5697-300	300"	27.75
5697-360	360"	30.25
5697-600	600"	42.75

## BNC MALE- ONE END ONLY

Pomona ACCESS 90445

Clamp nut and silicone gasket seal out moisture. Gold plated center contact and Teflon® insulation assure premium performance.

## BNC MALE RIGHT ANGLE CONNECTOR CABLE WITH MOLDED STRAIN RELIEF

Pomona ACCESS 90338




RATING: 500 VRMS Max., +50°C (+122°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC Connectors and strain relief materials same as Model 2249-C (p. 33).

Like 2249-C (p. 33) with right angle.

## BNC MALE 50 OHM CABLE WITH INSULATED PUSH-ON CONNECTOR

Pomona ACCESS 90511




RATING: 500 VRMS Max., +50°C (+122°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC Connector and strain relief materials same as Model 2249-C above.  
Outer shell of BNC is blue thermoplastic.

Unique locking feature assures secure retention with the convenience of a push-on connector.

## BNC MALE WITH MOLDED STRAIN RELIEF (ON RETRACTILE CABLE)

Use to extend BNC cables.

Pomona ACCESS 90349




RATING: 270 VDC-90 VAC cont. duty, +50°C (+122°F) Max.  
CABLE TYPE: Shielded microphone cable  
BNC Connectors and strain relief materials same as Model 2249-C (p. 33).

Pomona ACCESS 90349

Part No.	Extended Length	PRICE
4487-48	48"	41.00
4487-60	60"	41.00
4487-72	72"	41.00

## BNC MALE TO BNC FEMALE WITH MOLDED STRAIN RELIEF

Pomona ACCESS 90353



RATING: 500 VRMS Max., +50°C (+122°F) Max.  
CABLE TYPE: 50Ω RG58C/U, .195" O.D.  
BNC: Body: Brass, Tarnish Resistant Plating  
Dielectric: PTFE  
Center Contact: Male: Gold Plated Brass;  
Female: Gold Plated Beryllium Copper  
Strain Relief: PVC molded directly to cable and connectors.

Use to extend BNC Cables.

## BNC CONNECTOR - ONE END ONLY

## BNC MALE TO BNC MALE RIGHT ANGLE 50 OHM CABLE


Pomona ACCESS 90541



RATING: 500 VRMS Max., +80°C (+176°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC Connector materials same as Model BNC-C above.

## BNC FEMALE 50 OHM CABLE WITH MOLDED STRAIN RELIEF

Pomona ACCESS 90340



RATING: 500 VRMS Max., +50°C (+122°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC: Body: Brass, Tarnish Resistant Plating  
Dielectric: PTFE  
Center Contact: Gold Plated Beryllium Copper  
Strain Relief: PVC molded directly to cable and connectors.