



# High Reliability Optically Coupled Isolators

## Types 3N243, 3N244, 3N245, 3N243TX, 3N244TX, 3N245TX



### Features

- TX versions processed to Optek's military screening program patterned after MIL-PRF-19500
- TO-72 hermetically sealed package
- 1 kVDC electrical isolation

### Description

Each device in the series is a high reliability design optically coupled isolator consisting of an infrared emitting diode and an NPN silicon phototransistor mounted in a hermetically sealed TO-72 package.

Typical screening and lot acceptance tests are provided on page 13-4.

### Replaces

3N243R, 3N244R, 3N245R

### Absolute Maximum Ratings (T<sub>A</sub> = 25° C unless otherwise noted)

Input-to-Output Isolation Voltage .....	± 1.00 kVDC <sup>(1)</sup>
Storage Temperature Range .....	-65° C to +150° C
Operating Temperature Range .....	-55° C to +125° C
Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 sec. with soldering iron] .....	240° C <sup>(2)</sup>

### Input Diode

Forward DC Current .....	40 mA
Reverse Voltage .....	2.0 V
Power Dissipation .....	60 mW <sup>(3)</sup>

### Output Phototransistor

Continuous Collector Current .....	30 mA
Collector-Emitter Voltage .....	30 V
Emitter-Collector Voltage .....	5.0 V
Power Dissipation .....	200 mW <sup>(4)</sup>

### Notes:

- (1) Measured with input leads shorted together and output leads shorted together.
- (2) RMA flux is recommended. Duration can be extended to 10 sec. max. when flow soldering.
- (3) Derate linearly 0.60 mW/° C above 65° C.
- (4) Derate linearly 2.0 mW/° C above 25° C.
- (5) The input waveform is supplied by a generator with the following characteristics:  
Z<sub>OUT</sub> = 50 Ω, t<sub>r</sub> ≤ 15 ns, duty cycle ≅ 1%, pulse width ≅ 100 ms.

# Types 3N243, 3N244, 3N245 3N243TX, 3N244TX, 3N245TX

Electrical Characteristics ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	3N243TX			3N244TX			3N245TX			Units	Test Conditions
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max		
<b>Input Diode</b>												
$V_F$	Forward Voltage	0.80		1.30	0.80		1.30	0.80		1.30	V	$I_F = 10.0\text{ mA}$
		1.00		1.50	1.00		1.50	1.00		1.50	V	$I_F = 10.0\text{ mA}, T_A = -55^\circ\text{C}$
		0.70		1.20	0.70		1.20	0.70		1.20	V	$I_F = 10.0\text{ mA}, T_A = 100^\circ\text{C}$
$I_R$	Reverse Current			100			100			100	$\mu\text{A}$	$V_R = 2.0\text{ V}$
<b>Output Phototransistor</b>												
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	30			30			30			V	$I_C = 1.00\text{ mA}$
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage	5.0			5.0			5.0			V	$I_E = 100\ \mu\text{A}$
$I_{CEO}$	Collector Dark Current			100			100			100	nA $\mu\text{A}$	$V_{CE} = 10.0\text{ V}$ $V_{CE} = 10.0\text{ V}, T_A = 100^\circ\text{C}$
<b>Coupled</b>												
$I_{C(on)}$	On-State Collector Current	1.50			3.00			6.00			mA	$I_F = 10.0\text{ mA}, V_{CE} = 10.0\text{ V}$
		0.30			0.80			1.50			mA	$I_F = 3.0\text{ mA}, V_{CE} = 10.0\text{ V}$
		0.50			1.00			1.50			mA	$I_F = 10.0\text{ mA}, V_{CE} = 10.0\text{ V}, T_A = -55^\circ\text{C}$
		0.50			1.00			1.50			mA	$I_F = 10.0\text{ mA}, V_{CE} = 10.0\text{ V}, T_A = 100^\circ\text{C}$
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage			0.30							V	$I_F = 20\text{ mA}, I_C = 1.50\text{ mA}$
							0.30				V	$I_F = 20\text{ mA}, I_C = 3.0\text{ mA}$
									0.30		V	$I_F = 20\text{ mA}, I_C = 6.0\text{ mA}$
$I_{IO}$	Leakage Input-to-Output			100			100			100	nA	$V_{IO} = \pm 1.00\text{ kVDC}^{(1)}$
$C_{IO}$	Capacitance Input-to-Output			5.0			5.0			5.0	pF	$V_{IO} = 0\text{ V}, f = 1.00\text{ MHz}^{(1)}$
$t_r$	Output Rise Time			10.0			10.0			10.0	$\mu\text{s}$	$V_{CC} = 10.0\text{ V}, I_F = 10.0\text{ mA},^{(5)}$ $R_L = 100\ \Omega$
$t_f$	Output Fall Time			10.0			10.0			10.0	$\mu\text{s}$	

HI-REL OPTO COMPONENTS

Optek reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Optek Technology, Inc. 1215 W. Crosby Road Carrollton, Texas 75006 (214)323-2200 Fax (214)323-2396