




**Pomona
ACCESS**

FAX ON DEMAND This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (909) 469-2991. Enter the Pomona Access number (shown in italics) when prompted.

ALLIGATOR TEST CLIP TO SHEATHED BANANA PLUG PATCH CORD

NEW



Alligator length: 2.3", jaw opening .300"
Wire: High flex 18 AWG Silicone wire
RATING: 150V, 5 Amps, +50°C (+122°F) Max.
STD COLORS: -0 blk, -2 red, -4 yellow, -5 green, -6 blue.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90980 | 6489-48* | 48" | 4.50 |

EXTRA LARGE ALLIGATOR TEST CLIP TO SHEATHED BANANA PLUG PATCH CORD

NEW



Alligator length: 3.6", jaw opening: 0.8"
Conforms to IEC1010-2-031, Overvoltage Category III, 1000V, 10 Amps
Wire: High flex 18 AWG Silicone wire
STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90978 | 6570-36* | 36" | 12.00 |
| | 6570-60* | 48" | 13.00 |

EXTRA LARGE ALLIGATOR TEST CLIP PATCH CORD

NEW



Alligator length: 3.6", jaw opening: 0.8"
Conforms to IEC1010-2-031, Overvoltage Category III, 1000V, 10 Amps
Wire: High flex 18 AWG Silicone wire
STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90972 | 6569-36* | 36" | 14.00 |
| | 6569-60* | 48" | 15.00 |

RETRACTABLE SHEATH STACKING BANANA PLUG PATCH CORD




18 AWG wire, .144 O.D.
RATING: 1200V AC/DC Max., 7 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90665 | 5403-12* | 12" | 8.50 |
| | 5403-24* | 24" | 8.50 |
| | 5403-36* | 36" | 8.50 |
| | 5403-48* | 48" | 8.95 |
| | 5403-60* | 60" | 8.95 |

This retractable sheath banana plug has a stacking feature allowing the insertion of standard or other retractable plugs.


RETRACTABLE SHEATH BANANA PLUG PATCH CORD **CE**



18 AWG Wire, .144 O.D.
RATING: 1000V per IEC1010-2-031, 10 Amps, +80°C (+176°F) Max.
*STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|-----------|--------|-------|
| 90608 | 4911A-12* | 12" | 8.85 |
| | 4911A-18* | 18" | 8.85 |
| | 4911A-24* | 24" | 8.85 |
| | 4911A-36* | 36" | 8.85 |
| | 4911A-48* | 48" | 8.85 |
| | 4911A-60* | 60" | 8.85 |

SMD GRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD



Pincer opens to .090.
22 AWG Wire, .064 O.D.
RATING: 150V, 0.5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90468 | 5362-36* | 36" | 8.80 |


MINIGRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD **CE**



Features a slim (.36) body width. Hook attaches to component leads up to .060 O.D.
18 AWG Silicone insulated wire, .144 O.D.
RATING: 300V, 5 Amps per IEC1010-2-031
*STD. COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|-----------|--------|-------|
| 90481 | 6250A-12* | 12" | 6.70 |
| | 6250A-24* | 24" | 6.70 |
| | 6250A-36* | 36" | 6.70 |


MINIGRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD



Hook attaches to component leads up to .060 O.D.
20 AWG Wire, .087 O.D.
RATING: 300V, 5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90630 | 5270-12* | 12" | 6.30 |
| | 5270-24* | 24" | 6.30 |
| | 5270-36* | 36" | 6.30 |
| | 5270-48* | 48" | 6.70 |
| | 5270-60* | 60" | 6.70 |

MINIGRABBER® TEST CLIP TO STRAIGHT BANANA PLUG PATCH CORD



Features a slim (.36) body width. Hook attaches to component leads up to .060 O.D.
18 AWG Silicone insulated wire, .144 O.D.
RATING: 300V, 5 Amps
*STD. COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90484 | 6251-12* | 12" | 4.90 |
| | 6251-24* | 24" | 4.90 |
| | 6251-36* | 36" | 4.90 |

MINIGRABBER® TEST CLIP TO STRAIGHT BANANA PLUG PATCH CORD



Hook attaches to component leads up to .060 O.D.
20 AWG Wire, .087 O.D.
RATING: 300V, 5 Amps, +50°C (+122°F) Max.
*STD COLORS: -0 blk, -2 red.

| <i>Pomona ACCESS</i> | Part No. | Length | PRICE |
|----------------------|----------|--------|-------|
| 90600 | 4650-12* | 12" | 4.65 |
| | 4650-24* | 24" | 4.65 |
| | 4650-36* | 36" | 4.65 |
| | 4650-48* | 48" | 4.90 |
| | 4650-60* | 60" | 4.90 |